

内螺纹·外圈滑动表面带保护层



正常系列(PHS...)(SI...T/K)(NHS...)

杆端关节轴承



代码	类型		杆端		衬垫	内圈		
			材质	表面处理	材质	材质	热处理	
BNC06	内螺纹	外圈滑动表面带保护层	注油式	碳钢	镀环保白锌	铜	轴承钢	淬火
BNC01								
BNC07			自润滑	SUS304	—	PTFE(带铜网布)		
BNC02						SUS304	SUS304	
BNC03						PTFE	SUS440	



注油式
BNC06



自润滑
BNC01
BNC02
BNC03
BNC07



视角标准：第一视角

注油式(PHS...)

代码	型号	轴承规格	螺纹 旋向	d	B	d _k	C ₁	d ₂	G (6H)	h ₁	L ₃ (min)	L ₄	L ₅	W	d ₄	d ₅	R ₁	a°≈	静态径向 载荷容量(KN)	重量 (kg)
BNC06	PHS5		R (右旋)	5	8	7.7	6	16	M5×0.8	27	14	35	4	9	9	11	0.3	13	5.59	0.0165
	PHS6			6	9	9	6.75	18	M6×1.0	30	17	39	5	11	10	13			6.68	0.025
	PHS8			8	12	10.4	9	22	M8×1.25	36	17	47		14	12.5	16			9.8	0.043
	PHS10			10	14	12.9	10.5	26	M10×1.5	43	21	56		17	15	19			13.2	0.072
	PHS10-1		L (左旋)						M10×1.25				6.5							
	PHS12			12	16	15.4	12	30	M12×1.75	50	24	65		19	17.5	22			16.7	0.107
	PHS12-1								M12×1.25											
	PHS14			14	19	16.9	13.5	34	M14×2.0	57	27	74		22	20	25			20.6	0.16
	PHS14-1								M14×1.5				8							
	PHS16		R (右旋)	16	21	19.4	15	38	M16×2.0	64	33	83		24	22	27			25	0.21
	PHS16-1								M16×1.5											
	PHS18			18	23	21.9	16.5	42	M18×1.5	71	36	92		27	25	31			29.4	0.295
	PHS20			20	25	24.4	18	46	M20×1.5	77	40	100	10	30	27.5	34			34.3	0.38
	PHS22		L (左旋)	22	28	25.8	20	50	M22×1.5	84	43	111		32	30	38			41.2	0.49
	PHS25			25	31	29.6	22	60	M24×2.0	94	48	124	12	36	33.5	42			72.5	0.75
	PHS28			28	35	32.3	24	66	M27×2.0	103	53	136	14	37	46				75	0.98
	PHS30			30	37	34.8	25	70	M30×2.0	110	56	145	15	41					92.2	1.13
	PHS30-1								M27×2.0											

自润滑(SI...T/K)

代码	型号	轴承规格	螺纹 旋向	d	B	C ₁	d ₂	G (6H)	h ₁	L ₃ (min)	L ₄	L ₅	W	d ₄	d ₅	R ₁ (min)	a°≈	额定负荷(KN) 动负荷 静负荷	重量 (kg)
BNC01 BNC02 BNC03	SI5T/K*		R (右旋)	5	8	6.5	18.5	M5×0.8	27	10	36.5	4	9	8.5	11	0.3	13	4.6 4.8	0.016
	SI6T/K*			6	9	7	20	M6×1.0	30	12	40.5		11	10	13			6.1 6.5	0.022
	SI8T/K*			8	12	9	24	M8×1.25	36	16	48.5	5	14	12.5	16			8.5 9.5	0.047
	SI10T/K*			10	14	10.5	28.5	M10×1.5	43	20	58		17	15	19			9.7 12	0.077
	SI10T/K-1		L (左旋)					M10×1.25				6.5							
	SI12T/K*			12	16	12	32.5	M12×1.75	50	22	66.5		19	17.5	22			10.6 15	0.100
	SI12T/K-1							M12×1.25											
	SI14T/K*			14	19	13.5	36	M14×2.0	57	25	75		22	20	25			17 22	0.160
	SI14T/K-1							M14×1.5				8							
	SI16T/K*		R (右旋)	16	21	15.5	40	M16×2.0	64	28	85		23	22	27			19.7 27	0.220
	SI16T/K-1							M16×1.5											
	SI18T/K			18	23	16.5	45	M18×1.5	71	32	94.5	10	27	25	31			31.3 35	0.320
	SI20T/K			20	25	18	50	M20×1.5	77	33	102.5		30	27.5	34			29.8 40	0.420
	SI22T/K		L (左旋)	22	28	20	54	M22×1.5	84	37	111	12	32	30	38			40.2 48	0.488
	SI25T/K			25	31	22	60	M24×2.0	94	42	125		36	33.5	42			44 55	0.540
	SI28T/K			28	35	24	66	M27×2.0	103		136	14	37	46				52.2 65	0.720
	SI30T/K			30	37	25	70	M30×2.0	110	51	145	15	41					60.2 78	0.820
	SI30T/K-1							M27×2.0											1.100
BNC01	SI35T/K			35	43	28	81	M36×2.0	125	56	165.5	17	50	46	58			—	1.600
	SI40T/K			40	49	33	91	M42×2.0	142	60	187.5	19	55	53	65			—	2.400
	SI50T/K			50	60	45	117	M48×2.0	160	65	218.5	23	65	65	75			—	5.000

注：BNC03仅适用带“*”号规格。

自润滑(NHS...)

代码	型号	轴承规格	螺纹 旋向	d	B	C ₁	d ₂	G (6H)	h ₁	L ₃ (min)	L ₄	L ₅	W	d ₄	d ₅	R ₁	a°≈	静态径向 载荷容量(KN)	重量 (kg)
BNC07	NHS3		R (右旋)	3	6	4.5	12	M3×0.5	21	10	27	3	7	6.5	8			1.57	0.0065
	NHS4			4	7	5.3	14	M4×0.7	24	12	31		8	8	9.5			2.25	0.01
	NHS5			5	8	6	16	M5×0.8	27	14	36.5	4	9	9	11			3.92	0.0165
	NHS6			6	9	6.75	18	M6×1.0	30	17	39.5	5	11	10	13			5	0.025
	NHS8		L (左旋)	8	12	9	24	M8×1.25	36	17	49		14	12.5	16			7.45	0.043
	NHS10			10	14	10.5	28	M10×1.5	46	21	58		17	15	19			9.41	0.072
	NHS12			12	16	12	32	M12×1.75	50	24	66.5	6.5	19	17.5	22			11	0.107
	NHS14			14	19	13.5	38	M14×2.0	57	27	76		22	20	25			15.2	0.16
	NHS16		R (右旋)	16	21	15	40	M16×2.0	64	33	85		22	22	27			20.2	0.21
	NHS18			18	23	16.5	46	M18×1.5	71	36	94		27	25	31			25.2	0.295
	NHS20			20	25	18	50	M20×1.5	77	40	104	10	30	27.5	34			27.8	0.38
	NHS20																		



代码	型号	轴承规格	螺纹旋向	d
BNC01	SI5T/K		R(右旋)	5
BNC01	SI6T/K		L(左旋)	6

BNC01—SI5T/K—L



优惠价	数量	1~9	10~
价格	100%	另行报价	

未标价(元)



交货期	5
-----	---