


一字槽紧定螺钉

代码	类型	螺纹	材质		表面处理
			国标	相当	
TAY52	平端	粗牙	0Cr18Ni9	SUS304	—



适用标准: GB/T 73-1985

型号	M	L	n	h	d
TAY52	2	2 3 4 6 8	0.45	0.64	1
	2.5	3 4 5	0.6	0.72	1.5
	3	5 6 8 10 14	0.6	0.8	2
	4	4 6 8 16	0.8	1.12	2.5
	5	4 6 8 10	1	1.28	3.5
	6	6 8 20 30	1.2	1.6	4
	8	6 25	1.51	2	5.5



请按图示订货

代码	M	L
TAY52	3	5 6 8
	4	4 6

TAY52—M3—L5



未税价(元)

优惠价

数量	1~99	100~
价格	100%	另行报价




交货期

7

内六角喉塞

代码	类型	材质		表面处理
		国标	相当	
TAY36	内六角喉塞	ML40Cr	发黑	

规格M≥27, 材质为SCM440.




适用标准: DIN 906



Example 使用示例

压缩弹簧的压板

TAY36/TAN系列(P838)




保护未使用的螺孔

TAY36/TAN系列(P838)



齿轮箱等注油孔的盖子

TAY36/TAN系列(P838)




型号	M	P 螺距	h		S	L
			Min	Max		
TAY36	10	1.5	6	6.5	5	10
	12				6	
	14				8	
	16				10	
	18		6.5	7	12	
	20				6	
	22				6.5	
	24				7	

型号	M	P 螺距	h		S	L
			Min	Max		
TAY36	24	1.5	6	6.5	14	12
	26					
	27					
	28					
	30					
	33					

内六角圆柱头喉塞

代码	类型	材质	表面处理	适用标准
TAY40	内六角圆柱头喉塞	SUS304	—	DIN 908




视角标准: 第一视角



六角头喉塞

代码	类型	材质	表面处理	适用标准
TAY41	六角头喉塞	SUS304	—	DIN 910



视角标准: 第一视角



型号	M	P 螺距	D	K Min	h Min	S	L
12	17	7	6.15	12			
14	19	7.5	10.19				
16	21						
18	23	9	12.23				
20	25						
22	27						
24	29			4	17.23		
26	31						
27	32						
30	36						

型号	M	P 螺距	D	K Max	h Max	S	L
12	17	3.5	6.5	13	11		
14	19	8.5	19	22			
16	21						
18	23	10.5	24				
20	25						
22	27						
24	29						
26	31	15					
27	32						
30	36						

内六角圆柱头喉塞



请按图示订货

代码	M
TAY40	10 12

TAY40—M10



未税价(元)

优惠价

数量	1~49	50~
价格	100%	另行报价



交货期

5