


代码	类型	螺纹	强度等级	材质		表面处理
				国标	相当	
TAH26	全牙	粗牙	12.9	ML40Cr		发黑
TAH27				35CrMo	SCM435	
TAH51				A2-70	SUS304	—
TAH52				A4-70	SUS316	
TAH55				—	—	
TAH56	—	—	H62黄铜	酸洗		



TAH51/52/55 适用标准: DIN 933-1987
GB/T 5783-2016
ISO 4017-2011

其他 适用标准: GB/T 5783-2016



ML40Cr

型号	L					P	S	K	
代码	M						螺距		
TAH26	5	8 10 12 25 30 35 40					0.8	8	3.5
	6	12 16 20 25 30 35 40 45 50					1	10	4
	8	12 16 20 25 30 35 40 45 50 55 60 65					1.25	13	5.3
	10	16 20 25 30 35 40 45 50 55 60 90 100					1.5	16	6.4
	12	20 25 30 35 40 45 50 55 60 80 110 130 140 150					1.75	18	7.5
	14	30 35 40 45 50 55 60 65 70 80 90 100 110 120 130 140 150					2	21	8.8
	16	30 35 40 45 50 55 60 65 70					2	24	10
	18	40 45 50 55 60 65 70 75 80 85 90 100 110 120 130 140 150					2.5	27	11.5
	20	40 45 50 55 60 65 70 80 90 100 130 140					2.5	30	12.5
	22	50 55 60 65 70 80 90 100 110 120 130 140					3	34	14
	24	55 60 65 70 75 80 110 130					3	36	15

SUS304

型号	L					P	S	K	
代码	M						螺距		
TAH51	4	8 10 12 16 20 25 30 35 40 45					0.7	7	2.8
	5	8 10 12 16 20 25 30 35 40 45 50					0.8	8	3.5
	6	10 12 16 20 25 30 35 40 45 50 55 60 65 70 75					1	10	4
	8	12 16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100					1.25	13	5.3
	10	16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100					1.5	17	6.4
	12	20 25 30 35 40 45 50 55 60 65 70 75 80 90 100					1.75	19	7.5

SUS316

型号	L					P	S	K	
代码	M						螺距		
TAH52	4	8 10 12 16 20 25 30 35 40 45					0.7	7	2.8
	5	8 10 12 16 20 25 30 35 40 45					0.8	8	3.5
	6	10 12 16 20 25 30 35 40 45 50 55 60 65 70 75					1	10	4
	8	12 16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100					1.25	13	5.3
	10	16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100					1.5	17	6.4
	12	20 25 30 35 40 45 50 55 60 65 70 75 80 90 100					1.75	19	7.5

H62黄铜

型号	L					
代码	M					
TAH55	4	6 8 10 12 14 16				
	5	8 10 12 14 16				

请按图示订货

TAH56—M4—L12

SCM435

型号	L					P	S	K	
代码	M						螺距		
TAH27	8	20 25 30 40 45 50 120					1.25	13	5.3
	10	25 30 35 40 45 50 55 60 70 80					1.5	16	6.4
	12	25 30 35 40 45 50 55 60 65 70 80					1.75	18	7.5
	14	30 35 40 45 50 55 65 80					2	21	8.8
	16	30 35 40 45 50 55 60 65 70 75 80 90 100 120 130					2	24	10
	18	40 45 50 55 60 65 70					2.5	27	11.5
	20	40 45 50 55 60 65 70 80 90 100 110 120 210 230 240 250					2.5	30	12.5
	22	50 55 60 65 70 80 90 100					3	34	14
	24	50 55 60 65 70 75 80 90 100 120 130 150 180 210 220					3	36	15
	27	50 60 70 80 90 100 110 120 130 140 150 160 170 180 190 200					3.5	41	17
	30	55 60 65 70 75 80 85 90 95 100 110 120 130 140 150 160 170 180 190 200 210 220 230 240 250 290					3.5	46	18.7
	33	70 80 90 100 110 120 130 140 150 160 170 180 190 200					4	50	21
36	70 80 90 100 110 120 130 140 150 160 170 180 190 200 210 220 230 240 250					4	55	22.5	
42	80 90 100 110 120 130 140 150 160 170 180 190 200					4.5	65	26	

H62黄铜

型号	L					P	S	K	
代码	M						螺距		
TAH55	6	10 12 16 20 25 30					1	10	4
	8	20 25 30 35 40 50 60					1.25	13	5.3
	10	20 25 30 35 40 50 60					1.5	17	6.4
	12	30 35 40 45 50 60					1.75	19	7.5
	4	6 8 10 12 14 16 18 20 25 30 35 40					0.7	7	2.8
	5	8 10 12 14 16 18 20 25 30 35 40 45 50					0.8	8	3.5
TAH56	6	8 10 12 14 16 18 20 25 30 35 40 45 50 55 60					1	10	4
	8	10 12 16 18 20 25 30 35 40 45 50 55 60 65 70 75 80					1.25	13	5.3
	10	16 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90					1.5	16	6.4
	12	16 20 25 30 35 40 45 50 55 60 65 70 75 80					1.75	18	7.5
16	30 35 40 45 50 55 60 65 70 75 80 85 90 95 100					2	24	10	