


经济型防震脚杯

固定调节型 · 金属+橡胶底座型

重载型

代码	类型	材质			表面处理	
		外罩	螺杆	底部	外罩	螺杆
E-WAC51	固定调节型	S45C	S45C	橡胶(黄色)	镀锌	镀锌
E-WAC55				橡胶(白色)	镀锌	镀锌
E-WAC52				橡胶(黄色)	镀铬	镀铬
E-WAC56				TPU(黄色)	镀铬	镀铬
E-WAC71				橡胶(黄色)	—	—
E-WAC75		SUS304	SUS304	橡胶(白色)	—	—
E-WAC76				TPU(黄色)	—	—



视角标准：第一视角

型号	M	L	螺距	S	H	V	V1	承载 (Kg)	参考重量 (Kg/pcs)
代码	D								
E-WAC51 E-WAC55 E-WAC52 E-WAC56 E-WAC71 E-WAC75 E-WAC76	60	50						0.49	0.88
		75						0.52	0.91
		100	1.75	19		8	10	600	0.55
		125						0.58	0.93
	100	150		24				0.61	0.97
		75						0.51	1.01
		100	2	24		10	13	700	0.52
		125						0.54	1.05
	160	150						0.56	1.09
		75						0.52	1.15
		100	2	24		10	13	800	0.54
		125						0.56	1.1
	200	150						0.55	1.15
		75						0.53	1.18
		100	2.5	30		13	16	850	0.54
		125						0.55	1.25
	250	150						0.56	1.11
		75						0.72	1.24
		100						0.74	1.33
		125						0.76	1.42
	300	150	2	24		10	13	800	0.78
		200						0.8	1.53
		250						0.82	1.62
		300						0.84	1.75
	400	75						0.8	1.85
		100						0.82	1.54
		125						0.84	1.65
		150						0.86	1.76
	500	200	2.5	30		13	16	900	0.86
		250						0.88	1.89
		300						0.9	2.0
		350						0.9	2.12

型号	M	L	螺距	S	H	V	V1	承载 (Kg)	参考重量 (Kg/pcs)
代码	D								
E-WAC51 E-WAC55 E-WAC52 E-WAC56 E-WAC71 E-WAC75 E-WAC76	100	100						0.88	0.88
		125						0.91	0.91
		150						0.93	0.93
		200	3	36	32	16	19	950	0.97
	160	250						1.01	1.01
		300						1.05	1.05
		350						1.09	1.09
		400						1.15	1.15
	200	75						0.92	0.92
		100						0.95	0.95
		125						0.98	0.98
		150	2.5	30		13	16	1000	1.1
	250	200						1.15	1.15
		250						1.18	1.18
		300						1.25	1.25
		350						1.24	1.24
	300	100						1.11	1.11
		125						1.24	1.24
		150						1.33	1.33
		200	3	36	34	16	19	1050	1.42
	400	250						1.53	1.53
		300						1.62	1.62
		350						1.75	1.75
		400						1.85	1.85
	500	100						1.54	1.54
		125						1.65	1.65
		150						1.76	1.76
		200	3.5	46		24	24	1100	1.89
	600	250						2.0	2.0
		300						2.12	2.12
		350						2.24	2.24
		400						2.35	2.35

可选加工



型号	M	L
代码	D	
E-WAC51	60	50
E-WAC55	12	75

E-WAC51— D60— M12— L50

型号	M	L
代码	D	
E-WAC51	60	50
E-WAC55	12	75

E-WAC51— D60— M12— L50— WS

可选加工代码
WS WL BS



优惠价

数量	1~9	10~
价格	100%	另行报价

未税价(元)



交货期

1




可选加工

代码

技术说明

WS

螺杆末端加工外四角




选型方法 WS

M	n	e
10	6	
12		10
14	8	
16	10	12
20	12	13.5
24	14	15
30	18	22

WL

螺杆末端加工外六角




选型方法 WL

M	n1	e1
10	6	
12		10
14	9	
16	10	
20	13	14
24	16	18
30	20	21

BS

螺杆末端加工扳手槽



选型方法 BS

M	n2	ee	e2
10	8	8	
12			
14	12		12
16	13	10	
20	17		
24	20	15	18
30	26		

代码	技术说明																			
NS	螺杆末端加工内四角	<table><tr><th>选型方法</th><th>NS</th></tr><tr><td>M</td><td>n3 e3</td></tr><tr><td>10</td><td>5</td></tr><tr><td>12</td><td>6 10</td></tr><tr><td>14</td><td>8 12</td></tr><tr><td>16</td><td>10 13.5</td></tr><tr><td>20</td><td>15</td></tr><tr><td>24</td><td>10 15</td></tr><tr><td>30</td><td>20</td></tr></table>	选型方法	NS	M	n3 e3	10	5	12	6 10	14	8 12	16	10 13.5	20	15	24	10 15	30	20
	选型方法	NS																		
M	n3 e3																			
10	5																			
12	6 10																			
14	8 12																			
16	10 13.5																			
20	15																			
24	10 15																			
30	20																			
NL	螺杆末端加工内六角	<table><tr><th>选型方法</th><th>NL</th></tr><tr><td>M</td><td>n4 e4</td></tr><tr><td>10</td><td>4 5</td></tr><tr><td>12</td><td>6 8</td></tr><tr><td>14</td><td>8 10</td></tr><tr><td>16</td><td>10 12</td></tr><tr><td>20</td><td>12 15</td></tr><tr><td>24</td><td>12 15</td></tr><tr><td>30</td><td>16 18</td></tr></table>	选型方法	NL	M	n4 e4	10	4 5	12	6 8	14	8 10	16	10 12	20	12 15	24	12 15	30	16 18
	选型方法	NL																		
M	n4 e4																			
10	4 5																			
12	6 8																			
14	8 10																			
16	10 12																			
20	12 15																			
24	12 15																			
30	16 18																			
MS	铆死底座与螺杆	<table><tr><th>选型方法</th><th>MS</th></tr></table> ① 底座与螺杆铆死，可以提高底座与螺杆的连接刚度，但是底座与螺杆无法相对转动； ① 铆死后调节是底座也会随螺杆一起转动。 ① 不适用于万向类型、橡胶底座型和非铆接组装的脚杯。	选型方法	MS																
	选型方法	MS																		

① 请根据脚杯螺杆尺寸M进行加工参数的选择；

① 加工部不带镀层，有防锈漆；

① 工具可根据不同加工类型进行选择，可选用开口扳手、活动扳手、内六角扳手、内六角扳手等。