


日标

代码	类型	材质		硬度	适用标准
		国标	相当		
Y-JAD85	E型	3Cr13	SUS420J2	34~42HRC	JIS B 2805-1978



RoHS



视角标准：第一视角

型号		挡圈							适用轴(参考)					
代码	规格	d		D		H		t	d1的分类		d2	m	n	(min)
									大于	以下				
Y-JAD85	1.2	1.2		3	±0.1	1		0.3	±0.025	1.4	2	1.23	0.4	0.6
	1.5	1.5		4		1.3				2	2.5	1.53		0.8
	2	2	0 -0.09	5		1.7	0 -0.25	0.4	±0.03	2.5	3.2	2.05	+0.06 0	0.5
	2.5	2.5		6		2.1				3.2	4	2.55		1
	3	3		7		2.6				4	5	3.05		
	4	4		9	±0.2	3.5		0.6		5	7	4.05		
	5	5	0 -0.12	11		4.3	0 -0.30		±0.04	6	8	5.05	+0.075 0	1.2
	6	6		12		5.2				7	9	6.05		+0.1 0
	7	7		14		6.1		0.8		8	11	7.1		1.5
	8	8	0 -0.15	16		6.9	0 -0.35			9	12	8.1	+0.09 0	1.8
	9	9		18		7.8				10	13	9.1		2.1



请按图示订货

型号		d
代码	规格	
Y-JAD85	1.2	1.2
	1.5	1.5

Y-JAD85—1.2




未税价(元)

优惠价	
数量	1~45 46~
价格	100% 另行报价

国标

代码	类型	材质		适用标准
		国标	相当	
Y-JAD86	E型	0Cr18Ni9	SUS304	GB/T 896-1986



RoHS



视角标准：第一视角

型号		公称直径 d	极限偏差	挡圈尺寸					安装沟槽尺寸					轴径	
代码	规格			H		t		D max	d ₂		m		n≥		d ₁ >
				基本尺寸	极限偏差	基本尺寸	极限偏差		基本尺寸	极限偏差	基本尺寸	极限偏差			
Y-JAD86	1.5	1.5		1.2				4	1.5			1.0	2~2.5		
	2	2	0 -0.14	1.7	±0.125	0.4	+0.03 -0.06	5	2	+0.06 0	0.5		2.5~3.2		
	2.5	2.5		2.2			6	2.5			1.2	3.2~4			
	3	3	2.5		0.6	+0.04 -0.07	7	3		0.7		4~5			
	4	4	3.5		0.8	+0.04 -0.10	9	4		0.9		5~7			
	5	5	0 -0.18	4.5	±0.15			10	5	+0.075 0	+0.14 0	1.5	6~8		
	6	6	5.5				12	6				7~9			
	8	8	0 -0.22	7.5	±0.18	1.0	+0.05 -0.13	16	8	+0.09 0	1.1		9~12		
	9	9		8.0				18	9		2.0	10~14			
	12	12	0 -0.27	10.5	±0.215	1.2		24	12	+0.11 0		2.5	13~16		
15	15	13.0		1.5		+0.06 -0.15	30	15			1.6	3.0	16~20		



请按图示订货

型号		d
代码	规格	
Y-JAD86	1.5	1.5
	2	2

Y-JAD86—2



未税价(元)

优惠价	
数量	1~45 46~
价格	100% 另行报价