


XL/L/H型 ▶ 闭环型·精密型

梯形齿同步带


代码	类型	齿距	材质		颜色	使用温度
			主体	芯线	主体	
Y-EFA02	XL	5.08	橡胶	玻璃 纤维线	黑色	-20~80℃
	L	9.525				
	H	12.7				

- ① 精密型橡胶同步带具有一定导电功能。
② 为减少橡胶屑飞散，精密型橡胶同步带部分齿形齿面布为茶棕色，对强度及使用性能无影响。
③ 橡胶同步带芯线采用螺旋缠绕的方式排布，分切后会看到芯线层，不影响使用。



皮带宽度公差

皮带宽度(mm)	公差
3~30	±0.5
31~50	±0.8
51~100	±1.0



代码	齿形	齿距	2α	L	h	H	V	R _b	R _a
Y-EFA02	XL	5.08	50°	2.57	1.27	2.27	1.00	0.38	0.38
	L	9.525	40°	4.65	1.91	3.61	1.70	0.51	0.51
	H	12.7	40°	6.12	2.29	4.59	2.30	1.00	1.00



Y-EFA02-XL(齿距: 5.08)

型号	代码	皮带公称宽度	齿数	皮带周长
Y-EFA02-XL	30	6.4mm	30	152.40
	32	6.4mm	32	162.56
	34	6.4mm	34	172.72
	35	6.4mm	35	177.80
	37	6.4mm	37	187.96
	38	6.4mm	38	193.04
	39	6.4mm	39	198.12
	40	6.4mm	40	203.20
	41	6.4mm	41	208.28
	42	6.4mm	42	213.36
	43	6.4mm	43	218.44
	44	6.4mm	44	223.52
	45	6.4mm	45	228.60
	46	6.4mm	46	233.68
	47	6.4mm	47	238.76
	48	6.4mm	48	243.84
	49	6.4mm	49	248.92
	50	6.4mm	50	254.00
	51	6.4mm	51	259.08
	52	6.4mm	52	264.16
	53	6.4mm	53	269.24
	54	6.4mm	54	274.32
	55	6.4mm	55	279.40
	56	6.4mm	56	284.48
	57	6.4mm	57	289.56
	58	6.4mm	58	294.64
	59	6.4mm	59	299.72
	60	6.4mm	60	304.80
	61	6.4mm	61	309.88
	62	6.4mm	62	314.96
	63	6.4mm	63	320.04
	64	6.4mm	64	325.12
	65	6.4mm	65	330.20
	66	6.4mm	66	335.28
	67	6.4mm	67	340.36
	68	6.4mm	68	345.44
	69	6.4mm	69	350.52
	70	6.4mm	70	355.60
	71	6.4mm	71	360.68
	72	6.4mm	72	365.76
	73	6.4mm	73	370.84
	74	6.4mm	74	375.92
	75	6.4mm	75	381.00
	76	6.4mm	76	386.08
	77	6.4mm	77	391.16
	78	6.4mm	78	396.24
	79	6.4mm	79	401.32
	80	6.4mm	80	406.40
	81	6.4mm	81	411.48
	82	6.4mm	82	416.56
	83	6.4mm	83	421.64
	84	6.4mm	84	426.72
	85	6.4mm	85	431.80
	86	6.4mm	86	436.88
	87	6.4mm	87	441.96
	88	6.4mm	88	447.04
	89	6.4mm	89	452.12
	90	6.4mm	90	457.20
	91	6.4mm	91	462.28
	92	6.4mm	92	467.36
	93	6.4mm	93	472.44
	94	6.4mm	94	477.52
	95	6.4mm	95	482.60
	96	6.4mm	96	487.68
	97	6.4mm	97	492.76

Y-EFA02-XL(齿距: 5.08)

型号	代码	皮带公称宽度	齿数	皮带周长
Y-EFA02-XL	98	6.4mm	98	497.84
	99	6.4mm	99	502.92
	100	6.4mm	100	508.00
	101	6.4mm	101	513.08
	102	6.4mm	102	518.16
	103	6.4mm	103	523.24
	105	6.4mm	105	533.40
	106	6.4mm	106	538.48
	108	6.4mm	108	548.64
	109	6.4mm	109	553.72
	110	6.4mm	110	558.80
	114	6.4mm	114	579.12
	115	6.4mm	115	584.20
	117	6.4mm	117	594.36
	118	6.4mm	118	599.44
	120	6.4mm	120	609.60
	125	6.4mm	125	635.00
	127	6.4mm	127	645.16
	130	6.4mm	130	660.40
	135	6.4mm	135	685.80
	138	6.4mm	138	701.04
	140	6.4mm	140	711.20
	141	6.4mm	141	716.28
	145	6.4mm	145	736.60
	150	6.4mm	150	762.00
	155	6.4mm	155	787.40
	157	6.4mm	157	797.56
	160	6.4mm	160	812.80
	165	6.4mm	165	838.20
	166	6.4mm	166	843.28
	170	6.4mm	170	863.60
	174	6.4mm	174	883.92
	176	6.4mm	176	894.08
	180	6.4mm	180	914.40
	182	6.4mm	182	924.56
	185	6.4mm	185	939.80
	188	6.4mm	188	955.04
	192	6.4mm	192	975.36
	194	6.4mm	194	985.52
	195	6.4mm	195	990.60
	198	6.4mm	198	1005.84
	207	6.4mm	207	1051.56
	212	6.4mm	212	1076.96
	230	6.4mm	230	1168.40
	239	6.4mm	239	1214.12
	240	6.4mm	240	1219.20
	245	6.4mm	245	1244.60
	261	6.4mm	261	1325.88
	266	6.4mm	266	1351.28
	270	6.4mm	270	1371.60
	276	6.4mm	276	1402.08
	282	6.4mm	282	1432.56
	296	6.4mm	296	1503.68
	300	6.4mm	300	1524.00
	308	6.4mm	308	1564.64
	315	6.4mm	315	1600.20
	335	6.4mm	335	1701.80
	345	6.4mm	345	1752.60
	377	6.4mm	377	1915.16
	414	6.4mm	414	2103.12
	430	6.4mm	430	2184.40

Y-EFA02-L(齿距: 9.525)

型号	代码	皮带公称宽度	齿数	皮带周长
Y-EFA02-L	29	12.7mm	29	276.23
	33	12.7mm	33	314.33
	36	12.7mm	36	342.90
	40	12.7mm	40	381.00
	44	12.7mm	44	419.10
	46	12.7mm	46	438.15
	48	12.7mm	48	457.20
	50	12.7mm	50	476.25
	56	12.7mm	56	533.40
	58	12.7mm	58	552.45
	60	12.7mm	60	571.50
	62	12.7mm	62	590.55
	64	12.7mm	64	609.60
	68	12.7mm	68	647.70
	71	12.7mm	71	676.28
	72	12.7mm	72	685.80
	74	12.7mm	74	704.85
	76	12.7mm	76	723.90
	80	12.7mm	80	762.00
	84	12.7mm	84	800.10
	85	12.7mm	85	809.63
	86	12.7mm	86	819.15
	89	12.7mm	89	847.73
	90	12.7mm	90	857.25
	92	12.7mm	92	876.30
	96	12.7mm	96	914.40
	98	12.7mm	98	933.45
	100	12.7mm	100	952.50
	102	12.7mm	102	971.55
	104	12.7mm	104	990.60
	105	12.7mm	105	1000.13
	106	12.7mm	106	1009.65
	112	12.7mm	112	1066.80
	114	12.7mm	114	1085.85
	116	12.7mm	116	1104.90
	120	12.7mm	120	1143.00
	121	12.7mm	121	1152.53
	128	12.7mm	128	1219.20
	136	12.7mm	136	1295.40
	140	12.7mm	140	1333.50
	144	12.7mm	144	1371.60
	146	12.7mm	146	1390.65
	155	12.7mm	155	1476.38
	160	12.7mm	160	1524.00
	168	12.7mm	168	1600.20
	174	12.7mm	174	1657.35
	176	12.7mm	176	1676.40
	186	12.7mm	186	1771.65
	195	12.7mm	195	1857.38
	249	12.7mm	249	2371.73
	313	12.7mm	313	2981.33
	337	12.7mm	337	3209.93

Y-EFA02-H(齿距: 12.7)

型号	代码	皮带公称宽度	齿数	皮带周长
Y-EFA02-H	45	50.8mm	45	571.5
	46	50.8mm	46	584.2
	48	50.8mm	48	609.6
	49	50.8mm	49	622.3
	51	50.8mm	51	647.7
	54	50.8mm	54	685.8
	56	50.8mm	56	711.2
	60	50.8mm	60	762.0
	62	50.8mm	62	787.4
	63	50.8mm	63	800.1
	64	50.8mm	64	812.8
	66	50.8mm	66	838.2
	68	50.8mm	68	863.6
	70	50.8mm	70	889.0
	72	50.8mm	72	914.4
	74	50.8mm	74	939.8
	75	50.8mm	75	952.5
	78	50.8mm	78	990.6
	80	50.8mm	80	1016.0
	82	50.8mm	82	1041.4
	84	50.8mm	84	1066.8
	86	50.8mm	86	1092.2
	90	50.8mm	90	1143.0
	93	50.8mm	93	1181.1
	96	50.8mm	96	1219.2
	98	50.8mm	98	1244.6
	102	50.8mm	102	1295.4
	106	50.8mm	106	1346.2
	108	50.8mm	108	1371.6
	112	50.8mm	112	1422.4
	114	50.8mm	114	1447.8
	116	50.8mm	116	1473.2
	120	50.8mm	120	1524