

标准型 全不锈钢快拧接头



弯接头

外螺纹 常规款/S款

■ 常规款

代码	类型	材质
XES11	常规款 外螺纹 弯接头	SUS316
XES14		SUS304

① M5密封圈材质为FKM70。



视角标准：第一视角

型号	代码	D管外径	公称型号	d 适用软管内径	R	L1	L2	L3	S	B
(SUS316) XES11	4	2.5	M5	M5	M5	14	14	4	8	4
			1	R1/8	R1/8	19	16.7	7.5		
			M5	M5	M5	20.9	14.7	4		
	6	4	1	R1/8	R1/8	20.9	17.5	7.5	12	6
			2	R1/4	R1/4	22.3	19.5	9.5		
			3	R3/8	R3/8	20.9	24.9	10.5		
	8	6	1	R1/8	R1/8	22.2	17.8	7.5	14	6.5
			2	R1/4	R1/4	22.2	19.2	9.5		
			3	R3/8	R3/8	24.9	22.8	10.5		
	10	8	1	R1/8	R1/8	24.9	21	9.5	17	7.5
			2	R1/4	R1/4	24.9	22	10.5		
			3	R3/8	R3/8	24.9	29.7	12.5		
(SUS304) XES14	12	10	1	R1/8	R1/8	29.6	20.8	7.5	19	10
			2	R1/4	R1/4	29.6	22.8	9.5		
			3	R3/8	R3/8	31	23.8	10.5		
	16	13	1	R1/8	R1/8	33.5	26	10.5	22	12
			2	R1/4	R1/4	33.5	26.5	12.5		
			3	R3/8	R3/8	33.5	28	12.5		



请按图示订货 XES11-D8-1

型号	代码	D管外径	公称型号
XES11	8	8	1



未税价(元)

优惠价	数量	1~19	20~
价格	100%	另行报价	





交货期	9
-----	---

■ S款

代码	类型	材质
XES91	S款 外螺纹 弯接头	SUS316
XES94		SUS304

① 安装时可360°旋转方向。



视角标准：第一视角

型号		d	公称	R	L ₁	L ₂	L ₃	A	S ₁	S ₂	B
代码	D 管外径	适用软管 管内径	型号								
(SUS316) XES91	4	2.5	1	R1/8	14.5	16.1	8	7	10	8	4.5
			2	R1/4					14		
			3	R3/8					17		
	6	4	1	R1/8	15.5	18.5	8	9	12	10	6
			2	R1/4					14		
			3	R3/8					17		
(SUS304) XES94	8	6	1	R1/8	17.7	21	8	11	12	14	6.5
			2	R1/4					14		
			3	R3/8					17		
	10	6.5	1	R1/8	21	23.3	9	14	17	15	6.9
			2	R1/4					14		
			3	R3/8					17		

型号		d	公称		R	L ₁	L ₂	L ₃	A	S ₁	S ₂	B
代码	D	适用软管内径	型号									
(SUS316) XES91	10	8	3	R3/8	20.5	24.8	10	14	17	15	6.9	
			4	R1/2		26.3	11.5		22			
			2	R1/4		24.5	9		17			
	12	9	3	R3/8	21.5	26	10	15.8	17	17	7.5	
			4	R1/2		27.5	11.5		22			
			2	R1/4		24.5	9		17			
	(SUS304) XES94	10	8	3	R3/8	21.5	26	10	15.8	17	17	7.5
				4	R1/2		27.5	11.5		22		
				2	R1/4		24.5	9		17		
16		12	3	R3/8	27	29.5	10	20	22	22	9	
			4	R1/2		33.5	11.5		33.5			
			2	R1/4		29.5	10		33.5			



请按图示订货

型号	代码	D管外径	d 适用软管内径	公称型号
XES91	4	4	2.5	1

XES91-D4-d2.5-1



未税价(元)

优惠价	数量	1~19	20~
价格	100%	另行报价	



交货期	9
-----	---