


双圆环压缩弹簧 / 高寿命压缩弹簧

双圆环压缩弹簧

代码	类型	材质
YRW	双圆环压缩弹簧	SUS304

- 特点：可用于吊装、支撑的场景。
① 两端均未进行磨削加工。



视角标准：第一视角

型号	线径d	参考使用负载(N)
代码	D	
8	0.8	4.90
10	1.0	6.86
12	1.0	9.81
14	1.2	9.81
18	1.4	13.73
22	1.6	19.62
25	1.6	19.62

型号	线径d
代码	D
YRW	8
YRW	10

请按图示订货 YRW-D8-d0.8

数量	1~9	10~
价格	100%	另行报价


交货期
3

高寿命压缩弹簧

代码	类型		材质		表面处理	允许 位移量	弹簧常数 公差
			国标	相当			
YUG	外径基准型	标准型	0Cr18Ni9	SUS304-WPB	—	L×45%	±10%
YWG			琴钢丝	SWP	发黑		

- ① 压紧长度为参考值，制作时会有少许差异。
① 使用次数：1000万次。
① 两端均未磨削加工。
① 可广泛用作气动元件弹簧等。

D尺寸公差	L尺寸公差
D	L
5以下	±0.1
6以上	±0.2
50以下	±1
55以上	±2



视角标准：第一视角

型号	代码	D	L	d	压紧长度	F max	允许负载 Nmax	弹簧常数 N/mm
YUG	2	10	5	0.2	2	2.25	0.79	0.35
			10		3.4	4.5	0.79	0.18
			15		5	6.75	0.75	0.11
			20		5.8	9	0.85	0.09
			25		10.12	11.25	1.24	0.11
			30		12.19	13.5	1.22	0.09
	3	10	5	0.23	1.84	2.25	0.53	0.24
			10		2.99	4.5	0.53	0.12
			15		3.91	6.75	0.57	0.08
			20		5.25	9	0.84	0.09
			25		6.25	11.25	0.86	0.08
			30		7.25	13.5	0.86	0.06
YUG	4	10	5	0.25	8.25	15.75	0.88	0.06
			10		12	18	1.78	0.10
			15		2.75	4.5	0.37	0.08
			20		3.25	6.75	0.45	0.07
			25		5.1	9	0.92	0.10
			30		6	11.25	0.95	0.08
YUG	5	10	5	0.3	6.9	13.5	0.96	0.07
			10		9.1	15.75	1.89	0.12
			15		10.15	18	1.91	0.11
			20		11.2	20.25	1.92	0.10
			25		12.6	22.5	1.87	0.08
			30		16.4	24.75	3.19	0.13
YUG	6	10	5	0.35	17.6	27	3.21	0.12
			10		3.5	4.5	0.86	0.19
			15		3.85	6.75	1.13	0.17
			20		6.8	9	1.51	0.15
			25		7.6	11.25	1.65	0.15
			30		8.8	13.5	1.67	0.12
YUG	7	10	5	0.4	10.8	15.75	2.91	0.19
			10		12.15	18	2.92	0.16
			15		13.5	20.25	2.93	0.14
			20		14.85	22.5	2.93	0.13
			25		18	24.75	4.60	0.19
			30		19.5	27	4.59	0.17
YUG	8	10	5	0.45	22.5	31.5	4.60	0.15
			10		3.5	4.5	0.86	0.19
			15		3.85	6.75	1.13	0.17
			20		6.8	9	1.51	0.15
			25		7.6	11.25	1.65	0.15
			30		8.8	13.5	1.67	0.12
YUG	9	10	5	0.5	10.8	15.75	2.91	0.19
			10		12.15	18	2.92	0.16
			15		13.5	20.25	2.93	0.14
			20		14.85	22.5	2.93	0.13
			25		18	24.75	4.60	0.19
			30		19.5	27	4.59	0.17
YUG	10	10	5	0.55	22.5	31.5	4.60	0.15
			10		3.5	4.5	0.86	0.19
			15		3.85	6.75	1.13	0.17
			20		6.8	9	1.51	0.15
			25		7.6	11.25	1.65	0.15
			30		8.8	13.5	1.67	0.12

型号	代码	D	L	d	压紧长度	F max	允许负载 Nmax	弹簧常数 N/mm
YUG	2	10	10	0.45	4.5	4.5	1.38	0.31
			15		5.4	6.75	1.61	0.24
			20		8	9	2.33	0.26
			25		9.5	11.25	2.36	0.21
			30		10.5	13.5	2.52	0.19
			35		13.2	15.75	3.80	0.24
YUG	3	10	10	0.55	14.3	18	3.96	0.22
			15		15.4	20.25	4.09	0.20
			20		16.5	22.5	4.21	0.19
			25		18.6	24.75	6.51	0.26
			30		19.8	27	6.62	0.25
			35		21.6	31.5	7.02	0.22
YUG	4	10	10	0.6	24.6	36	6.95	0.19
			15		4.6	4.5	1.67	0.37
			20		6.05	6.75	1.67	0.25
			25		8.4	9	2.34	0.26
			30		9.6	11.25	2.48	0.22
			35		10.8	13.5	2.58	0.19
YUG	5	10	10	0.65	12.35	15.75	3.95	0.25
			15		13.65	18	4.01	0.22
			20		14.95	20.25	4.07	0.20
			25		16.25	22.5	4.12	0.18
			30		18.2	24.75	5.94	0.24
			35		18.9	27	6.21	0.23
YUG	6	10	10	0.7	20.3	31.5	6.68	0.21
			15		21.7	36	7.09	0.20
			20		6.5	6.75	1.88	0.28
			25		8.4	9	2.67	0.30
			30		9.8	11.25	2.73	0.24
			35		11.2	13.5	2.78	0.21
YUG	7	10	10	0.75	12.75	15.75	4.03	0.26
			15		14.25	18	4.03	0.22
			20		15.75	20.25	4.03	0.20
			25		17.25	22.5	4.03	0.18
			30		18.4	24.75	5.82	0.24
			35		19.2	27	6.05	0.22
YUG	8	10	10	0.8	20	31.5	6.74	0.21
			15		21.6	36	7.06	0.20
			20		6.5	6.75	1.88	0.28
			25		8.4	9	2.67	0.30
			30		9.8	11.25	2.73	0.24
			35		11.2	13.5	2.78	0.21



型号	代码	D	L	d
YUG	YUG	10	15	0.23

YUG-D3-L5



数量	1~9	10~
价格	100%	另行报价

交货期
5