


代码	类型		材质	
			国标	相当
YAS01	环形弹簧	无连接	0Cr18Ni9	SUS304-WPB
YAS02		螺旋连接		
YAS03		焊接连接		





用途：橡皮筋的功能、油封的弹簧以及其他用途。

无连接  
YAS01





螺旋连接  
YAS02



连接部放大图

焊接连接  
YAS03



视角标准：第一视角

无连接

代码	型号		长度L
	D	线径d	
YAS01	3	0.4	500
		0.4	1000
	4	0.5	500
		0.5	1000
	5	0.7	500
		0.7	1000
	6	0.8	750
		0.8	1500
	8	0.9	750
		0.9	1500
10	1	750	
	1	1500	

螺旋连接/焊接连接

代码	型号		线径d	适用直径	初始张力(N)	弹簧常数 N/mm
	S	D				
螺旋连接 YAS02 焊接连接 YAS03	16	2	0.35	18~20	1.2	0.18
		2.5	0.4			
	18	2	0.35	20~22	1.2	0.16
		2.5	0.4			
	20	2	0.35	22~25	1.2	0.15
		2.5	0.4			
	25	2	0.35	28~31	1.2	0.12
		2.5	0.4			
	30	2	0.35	33~38	1.3	0.11
		2.5	0.4			
	35	2	0.35	39~44	1.2	0.09
		2.5	0.4			
	40	2.5	0.4	44~51	1.3	0.07
		3	0.5			
	50	2.5	0.4	55~64	1.3	0.06
		3	0.5			
	60	2.5	0.4	66~76	2.2	0.10
		3	0.5			
	70	2.5	0.4	77~89	1.3	0.05
		3	0.5			
85	2.5	0.4	93~108	2.2	0.09	
	3	0.5				
100	2.5	0.4	110~128	1.3	0.03	
	3	0.5				

S值、初始张力、弹簧常数是加工成环形的计算值。



请按图示订货

无连接

代码	D	线径d	长度L
YAS01	3	0.4	1000

YAS01-D3-d0.4-L500

螺旋连接

代码	S	D	线径d
YAS02	16	2	0.35
		2.5	0.4

YAS02-S16-D2-d0.35



优惠价

数量	1~19	20~
价格	100%	另行报价

未税价(元)



交货期

3