


经济型100级眼型旋转吊环

代码	类型	材质	表面处理
TCF45	经济型100级眼型旋转吊环	合金钢	烤漆(橘红色)



① 因烤漆工艺,可能会导致产品吊装处部分区域未能烤漆。



视角标准: 第一视角

型号		M	A	B	C	D	E	F	W	S
代码	规格									
TCF45	0.3T	M8	37	25	8.5	11	13	25	47	6
	0.4T	M10	37	25	8.5	11	17	25	47	6
	0.75T	M12	45	30	10	13	21	35	56	8
	1.5T	M16	52	35	14	15	27	39	65	10
	2.3T	M20	60	40	16	17	30	46	75	12
	3.2T	M24	69	48	19	21	36	53	90	14
	4.5T	M30	92	60	24	26	45	64	100	17
	7T	M36	103	72	29	32	54	75	135	22
	9T	M42	127	82	34	38	63	90	158	24
	12T	M48	139	94	38	43	68	100	180	27

工作极限载荷

吊环 安装方式											
吊环数量 起吊角度		1 0°	2 0°	1 90°	2 90°	2 ≤90°	2 90~120°	2 ≤90°	3~4 ≤90°	3~4 90~120°	3~4 ≤90°
型号		工作安全极限载荷(吨)									
代码	规格										
TCF45	0.3T	0.8	1.6	0.3	0.6	0.42	0.3	0.3	0.63	0.45	0.3
	0.4T	1	2	0.4	0.8	0.56	0.4	0.4	0.8	0.6	0.4
	0.75T	2	4	0.75	1.5	1	0.7	0.7	1.5	1.3	0.7
	1.5T	4	8	1.5	3	2.1	1.5	1.5	3.1	2.2	1.5
	2.3T	6	12	2.3	4.6	3.2	2.3	2.3	4.8	3.4	2.3
	3.2T	8	16	3.2	6.4	4.5	3.2	3.2	6.7	4.8	3.2
	4.5T	12	24	4.5	9	6.3	4.5	4.5	9.4	6.7	4.5
	7T	16	32	7	14	9.8	7	7	14.7	10.5	7
	9T	24	48	9	18	12.6	9	9	18.9	13.5	9
	12T	32	64	12	24	16.8	12	12	25	18	12



型号	
代码	规格
TCF45	0.3T
	0.4T

TCF45 — 0.3T



优惠价

数量	1~9	10~
价格	100%	另行报价

交货期
7

垫圈·吊环
螺母·螺帽

C2