

金属垫圈

标准型・尺寸指定 普通型/精密型

代码	类型		材质		硬度	表面处理
			国标	相当		
Y-JCA51	标准型	普通型	45	S45C	—	—
Y-JCA52					43~48HRC	—
Y-JCA53					—	发黑
Y-JCA54					43~48HRC	—
Y-JCA55					—	无电解镀镍
Y-JCA56		—	43~48HRC	—		
Y-JCA57		—	0Cr18Ni9	SUS304	—	本色阳极氧化
Y-JCA58		—	LY11	A2017	—	黑色阳极氧化
Y-JCA59		—	9CrWMn	SKS3	53HRC~	发黑
Y-JCA60		尺寸指定			—	无电解镀镍
Y-JCA61	—				—	
Y-JCA71	—		—			
Y-JCA72	精密型	—	—	43~48HRC	—	
Y-JCA73				—	—	
Y-JCA74				—	发黑	
Y-JCA75				43~48HRC	—	
Y-JCA76				—	无电解镀镍	
Y-JCA77		—	0Cr18Ni9	SUS304	—	—
Y-JCA78		—	LY11	A2017	—	本色阳极氧化
Y-JCA80		—	9CrWMn	SKS3	53HRC~	发黑
Y-JCA81		—			无电解镀镍	






① 如对防锈有要求，请优先选用不锈钢材质或无电解镀镍产品。

普通型

Y-JCA51/52/53/54
Y-JCA55/56/57/58
Y-JCA59/60/61

精密型

Y-JCA71/72/73/74
Y-JCA75/76/77/78
Y-JCA80/81



普通型

型号		V 最小单位0.5 (V尺寸3以上)	T 最小单位0.1
代码	D 最小单位0.5		
	3.0~10.0		
	10.5~20.0	0(无孔)	
Y-JCA51 Y-JCA57	20.5~30.0	1.5	1.0~12.0
Y-JCA52 Y-JCA58	30.5~40.0	2.0	
Y-JCA53 Y-JCA59	40.5~50.0	2.6	
Y-JCA54 Y-JCA60	50.5~60.0	最小单位0.5	
Y-JCA55 Y-JCA61	60.5~80.0	3.0~100.0	5.0~12.0
Y-JCA56	80.5~100.0		

精密型

型号		V 最小单位0.5 (V尺寸3以上)	T 最小单位0.1
代码	D 最小单位0.5		
	3.0~10.0		
	10.5~20.0	0(无孔)	
Y-JCA71 Y-JCA76	20.5~30.0	1.5	1.0~12.0
Y-JCA72 Y-JCA77	30.5~40.0	2.0	
Y-JCA73 Y-JCA78	40.5~50.0	2.6	
Y-JCA74 Y-JCA80	50.5~60.0	最小单位0.5	
Y-JCA75 Y-JCA81	60.5~80.0	3.0~100.0	5.0~12.0
	80.5~100.0		



可选加工

代码	技术说明
VC	变更内径公差 选型方法 VC ① 内径公差由 $V_{H7}^{+0.3}$ 变更为 V_{H7} 。
DC (g6) DE (h7)	变更外径公差 选型方法 DC或DE ① 外径公差由 $D_{h7}^{+0.2}$ 变更为 D_{g6} 或 D_{h7} 。

代码	技术说明																																				
KA	增加避让键槽	选型方法	KA																																		
		<table><tr><th>V</th><th>b</th><th>t</th><th>D-V</th></tr><tr><td>8~10.5</td><td>3</td><td>2.0</td><td>7以上</td></tr><tr><td>11~12.5</td><td>4</td><td>2.5</td><td>8以上</td></tr><tr><td>13~17.5</td><td>5</td><td>3.0</td><td>10以上</td></tr><tr><td>18~22.5</td><td>6</td><td>3.5</td><td>12以上</td></tr><tr><td>23~30.5</td><td>8</td><td></td><td></td></tr><tr><td>31~38.5</td><td>10</td><td>4.0</td><td>14以上</td></tr><tr><td>39~42.5</td><td>12</td><td></td><td></td></tr><tr><td>43~49.5</td><td>14</td><td>4.5</td><td>16以上</td></tr></table>	V	b	t	D-V	8~10.5	3	2.0	7以上	11~12.5	4	2.5	8以上	13~17.5	5	3.0	10以上	18~22.5	6	3.5	12以上	23~30.5	8			31~38.5	10	4.0	14以上	39~42.5	12			43~49.5	14	4.5
V	b	t	D-V																																		
8~10.5	3	2.0	7以上																																		
11~12.5	4	2.5	8以上																																		
13~17.5	5	3.0	10以上																																		
18~22.5	6	3.5	12以上																																		
23~30.5	8																																				
31~38.5	10	4.0	14以上																																		
39~42.5	12																																				
43~49.5	14	4.5	16以上																																		
DA ()	单面切割	选型方法	DA10																																		
		① DA最小单位1																																			
DB ()	双面切割	选型方法	DB10																																		
		① DB最小单位1																																			

普通型

代码	D	V	T
Y-JCA51	10.5~20.0	0	1.0~12.0
Y-JCA52	20.5~30.0	2.0	2.6
Y-JCA51—D18—V2.6—T2.1			

优惠价

数量	1~99	100~
价格	100% 另行报价	

未税价(元)

可选加工(精密型)

代码	D	V	T	可选加工代码
Y-JCA71	10.5~20.0	0	1.0~12.0	KA DA DB ()
Y-JCA72	20.5~30.0	2.0	2.6	VC
Y-JCA71—D18—V2.6—T2.1—VC				



请按图示订货