


代码	类型	螺纹	材质		表面处理	适用标准	强度等级
			国标	相当			
TBK50			35	S35C	镀镍		
TBK51			45	S45C	发黑		
TBK52					镀锌	DIN 934-1987	
TBK54			0Cr17Ni12Mo2	SUS316			
TBK55			0Cr18Ni9	SUS304			
TBK56						GB/T 6170-2015	
TBK67	标准型	粗牙	黄铜			DIN 934-1987	
TBK57					发黑	GB/T 6170-2015	
TBK64			35K(碳钢)		镀蓝白锌	DIN 934-1987	10级
TBK63					发黑		
TBK66			10B21		镀蓝白锌	GB/T 6170-2015	12级
TBK68			35CrMo		发黑		
TBK69							



视角标准：第一视角

DIN 934-1987

型号		P	m		S		e
代码	M	螺距	(max)	(min)	(max)	(min)	(min)
(S35C)	2*	0.4	1.6	1.35	4	3.82	4.32
	2.5*	0.45	2	1.75	5	4.82	5.45
	3	0.5	2.4	2.15	5.5	5.32	6.01
	4	0.7	3.2	2.9	7	6.78	7.66
	5	0.8	4	3.7	8	7.78	8.79
(S45C)	6	1	5	4.7	10	9.78	11.05
	8	1.25	6.5	6.14	13	12.73	14.38
	10	1.5	8	7.64	17	16.73	18.9
	12	1.75	10	9.64	19	18.67	21.1
	16	2	13	12.3	24	23.67	26.75
(SUS316)	20	2.5	16	14.9	30	29.16	32.95
	24	3	19	17.7	36	35	39.55
	3	0.5	2.4	2.15	5.5	5.32	6.01
	4	0.7	3.2	2.9	7	6.78	7.66
	5	0.8	4	3.7	8	7.78	8.79
(SUS304)	6	1	5	4.7	10	9.78	11.05
	8	1.25	6.5	6.14	13	12.73	14.38
	10	1.5	8	7.64	17	16.73	18.9
	12	1.75	10	9.64	19	18.67	21.1
	16	2	13	12.3	24	23.67	26.75
(黄铜)	20	2.5	16	14.9	30	29.16	32.95
	24	3	19	17.7	36	35	39.55
	2	0.4	1.6	1.35	4	3.82	4.32
	2.5	0.45	2	1.75	5	4.82	5.45
	3	0.5	2.4	2.15	5.5	5.32	6.01
(TBK67)	4	0.7	3.2	2.9	7	6.78	7.66
	5	0.8	4	3.7	8	7.78	8.79
	6	1	5	4.7	10	9.78	11.05
	8	1.25	6.5	6.14	13	12.73	14.38
	10	1.5	8	7.64	17	16.73	18.9
(TBK63)	12	1.75	10	9.64	19	18.67	21.1
	8	1.25	6.5	6.14	13	12.73	14.38
	10	1.5	8	7.64	17	16.73	18.9
	12	1.75	10	9.64	19	18.67	21.1
	16	2	13	12.3	24	23.67	26.75
(TBK66)	20	2.5	16	14.9	30	29.16	32.95
	2	0.4	1.6	1.35	4	3.82	4.32
	2.5	0.45	2	1.75	5	4.82	5.45
	3	0.5	2.4	2.15	5.5	5.32	6.01
	4	0.7	3.2	2.9	7	6.78	7.66
(TBK54)	5	0.8	4	3.7	8	7.78	8.79
	6	1	5	4.7	10	9.78	11.05
	8	1.25	6.5	6.14	13	12.73	14.38
	10	1.5	8	7.64	17	16.73	18.9
	12	1.75	10	9.64	19	18.67	21.1
(TBK55)	16	2	13	12.3	24	23.67	26.75
	20	2.5	16	14.9	30	29.16	32.95
	24	3	19	17.7	36	35	39.55
	3	0.5	2.4	2.15	5.5	5.32	6.01
	4	0.7	3.2	2.9	7	6.78	7.66
(TBK56)	5	0.8	4	3.7	8	7.78	8.79
	6	1	5	4.7	10	9.78	11.05
	8	1.25	6.5	6.14	13	12.73	14.38
	10	1.5	8	7.64	17	16.73	18.9
	12	1.75	10	9.64	19	18.67	21.1
(TBK57)	16	2	13	12.3	24	23.67	26.75
	20	2.5	16	14.9	30	29.16	32.95
	24	3	19	17.7	36	35	39.55
	3	0.5	2.4	2.15	5.5	5.32	6.01
	4	0.7	3.2	2.9	7	6.78	7.66
(TBK64)	5	0.8	4	3.7	8	7.78	8.79
	6	1	5	4.7	10	9.78	11.05
	8	1.25	6.5	6.14	13	12.73	14.38
	10	1.5	8	7.64	17	16.73	18.9
	12	1.75	10	9.64	19	18.67	21.1
(TBK65)	16	2	13	12.3	24	23.67	26.75
	20	2.5	16	14.9	30	29.16	32.95
	24	3	19	17.7	36	35	39.55
	3	0.5	2.4	2.15	5.5	5.32	6.01
	4	0.7	3.2	2.9	7	6.78	7.66
(TBK66)	5	0.8	4	3.7	8	7.78	8.79
	6	1	5	4.7	10	9.78	11.05
	8	1.25	6.5	6.14	13	12.73	14.38
	10	1.5	8	7.64	17	16.73	18.9
	12	1.75	10	9.64	19	18.67	21.1
(TBK67)	16	2	13	12.3	24	23.67	26.75
	20	2.5	16	14.9	30	29.16	32.95
	24	3	19	17.7	36	35	39.55
	3	0.5	2.4	2.15	5.5	5.32	6.01
	4	0.7	3.2	2.9	7	6.78	7.66
(TBK68)	5	0.8	4	3.7	8	7.78	8.79
	6	1	5	4.7	10	9.78	11.05
	8	1.25	6.5	6.14	13	12.73	14.38
	10	1.5	8	7.64	17	16.73	18.9
	12	1.75	10	9.64	19	18.67	21.1
(TBK69)	16	2	13	12.3	24	23.67	26.75
	20	2.5	16	14.9	30	29.16	32.95
	24	3	19	17.7	36	35	39.55
	3	0.5	2.4	2.15	5.5	5.32	6.01
	4	0.7	3.2	2.9	7	6.78	7.66

① 带*的规格不适用TBK50。

① 带*规格不适用TBK51。



请按图示订货

型号	代码	M
	TBK54	20
	TBK54	(24)
	TBK54—M24	



未税价(元)

优惠价	数量	1~4	5~
	价格	100%	另行报价



① TBK50



① 其余



① 其余

GB/T 6170-2015

型号		P	m		S		e	
代码	M	螺距	(max)	(min)	(max)	(min)	(min)	
(SUS304)	(2)*	0.4	1.6	1.35	4	3.82	4.32	
	4*	0.7	3.2	2.9	7	6.78	7.66	
	5*	0.8	4.7	4.4	8	7.78	8.79	
	6*	1	5.2	4.9	10	9.78	11.05	
	8*	1.25	6.8	6.44	13	12.73	14.38	
	10*	1.5	8.4	8.04	16	15.73	17.77	
	12*	1.75	10.8	10.37	18	17.73	20.03	
	14*	2	12.8	12.1	21	20.67	23.36	
	16*		14.8	14.1	24	23.67	26.75	
	18*	2.5	15.8	15.1	27	26.16	29.56	
20*	18		16.9	30	29.16	32.95		
(35K(碳钢)·发黑)	22	2.5	19.4	18.1	34	33	37.29	
	24*		21.5	20.2	36	35	39.55	
	27*	3	23.8	22.5	41	40	45.2	
	30*		25.6	24.3	46	45	50.85	
	33	3.5	28.7	27.4	50	49	55.37	
	36*		4	31	29.4	55	53.8	60.79
	(42)*	4.5	34	32.4	65	63.1	71.3	
	(35K(碳钢)·镀蓝白锌)	3	0.5	2.4	2.15	5.5	5.32	6.01
		4	0.7	3.2	2.9	7	6.78	7.65
	(10B21·发黑)	6	1	5.2	4.9	10	9.78	11.05
8		1.25	6.8	6.44	13	12.73	14.38	
10		1.5	8.4	8.04	16	15.73	17.77	
12		1.75	10.8	10.37	18	17.73	20.03	
14		2	12.8	12.1	21	20.67	23.36	
16			14.8	14.1	24	23.67	26.75	
18		2.5	15.8	15.1	27	26.16	29.56	
20			18	16.9	30	29.16	32.95	
22		3	19.4	18.1	34	33	37.29	
24			21.5	20.2	36	35	39.55	
(35CrMo·镀蓝白锌)	4	0.7	3.2	2.9	7	6.78	7.65	
	6	1	5.2	4.9	10	9.78	11.05	
	8	1.25	6.8	6.44	13	12.73	14.38	
	10	1.5	8.4	8.04	16	15.73	17.77	
(35CrMo·发黑)	12	1.75	10.8	10.37	18	17.73	20.03	
	14	2	12.8	12.1	21	20.67	23.36	
	16		14.8	14.1	24	23.67	26.75	
	18	2.5	15.8	15.1	27	26.16	29.56	
	20		18	16.9	30	29.16	32.95	
	22	3	19.4	18.1	34	33	37.29	
	24		21.5	20.2	36	35	39.55	
	27	3.5	23.8	22.5	41	40	45.2	
	30		25.6	24.3	46	45	50.85	
	33	4	28.7	27.4	50	49	55.37	
36	31		29.4	55	53.8	60.79		
(TBK69)	39	4.5	33.4	31.8	60	58.8	66.44	
	42		34	32.4	65	63.1	71.3	
	45	5	36	34.4	70	68.1	76.95	
	48		38	36.4	75	73.1	82.6	