



代码		螺纹	材质		硬度	表面处理
平端	锥端		国标	相当		
TAY01	TAY11	粗牙	ML40Cr		45HRC~	发黑
TAY02	TAY12		0Cr18Ni9	SUS304	—	—

平端
TAY01/02

① 适用标准: DIN 913-1980

锥端
TAY11/12

① 适用标准: DIN 914-1980

TAY01




TAY02



TAY11



TAY12



视角标准: 第一视角

平端(ML40Cr)

代码	型号	M	L	S		d	
				Max	Min	Max	Min
TAY01	2	2	2 3 4 5	0.902	0.889	1	0.75
	2.5	2.5	3 4 5 6 8	1.295	1.27	1.5	1.25
	3	3	3 4 5 6 8 10 12 16 20	1.545	1.52	2	1.75
	4	4	3 4 5 6 8 10 12 16 20	2.045	2.02	2.5	2.25
	5	5	4 5 6 8 10 12 16 20 25 30	2.56	2.52	3.5	3.2
	6	6	5 6 8 10 12 16 20 25 30 35 40 45 50	3.08	3.02	4	3.7
	8	8	6 8 10 12 16 20 25 30 35 40 45 50	4.095	4.02	5.5	5.2
	10	10	8 10 12 16 20 25 30 35 40 45 50	5.095	5.02	7	6.64
	12	12	10 12 16 20 25 30 35 40 45 50 60 70	6.095	6.02	8	8.14
	16	16	16 20 25 30 35 40 45 50 60 70	8.115	8.025	12	11.57

平端(SUS304)

代码	型号	M	L	S		d	
				Max	Min	Max	Min
TAY02	2	2	2 3 4 5 6 8 10 12	0.902	0.889	1	0.75
	2.5	2.5	2 3 4 5 6 8 10 12	1.295	1.27	1.5	1.25
	3	3	3 4 5 6 8 10 12 16 20 25	1.545	1.52	2	1.75
	4	4	3 4 5 6 8 10 12 16 20 22 25 30 35 40	2.045	2.02	2.5	2.25
	5	5	3 4 5 6 8 10 12 14 16 20 25 30 35 40 50	2.56	2.52	3.5	3.2
	6	6	4 5 6 8 10 12 16 18 20 25 30 35 40 45 50 60 70	3.08	3.02	4	3.7
	8	8	5 6 8 10 12 16 20 25 30 35 40 45 50 60 70 80	4.095	4.02	5.5	5.2
	10	10	6 8 10 12 16 20 25 30 35 40 45 50 55 60	5.095	5.02	7	6.64
	12	12	8 10 12 16 20 25 30 35 40 45 50 55	6.095	6.02	8	8.14
	16	16	12 16 20 25 30 35 40 45 50	8.115	8.025	12	11.57

h尺寸表(TAY01/02)

M	2		2.5		3		4		5		6		8		10		12		16	
L	≤3	>3	≤3	>3	≤4	>4	≤5	>5	≤6	>6	≤6	>6	≤6	>6	≤8	>8	≤12	>12	≤16	>16
h(min)	0.8	1.7	1.2	2	1.2	2	1.5	2.5	2	3	2	3.5	3	5	4	6	4.8	8	6.4	10

锥端(ML40Cr)

代码	型号	M	L	S		d	
				Max	Min	Max	Min
TAY11	2.5	2.5	6	1.295	1.27		
	3	3	3 4 5 6 8 10 12 20	1.545	1.52		
	4	4	4 5 6 8 10 12 16	2.045	2.02		
	5	5	5 6 8 10 12 16 20	2.56	2.52		
	6	6	6 8 10 12 16 20 25 30 35 40	3.08	3.02	1.5	0.9
	8	8	8 10 12 16 20 25 30	4.095	4.02	2	1.4
	10	10	10 12 16 20 25 30	5.095	5.02	2.5	1.9
	12	12	12 16 20 25 30 35 40	6.095	6.02	3	2.4
	16	16	16 20 25 30 35 40 45 50	8.115	8.025	4	3.25

锥端(SUS304)

代码	型号	M	L	S		d	
				Max	Min	Max	Min
TAY12	2	2	2 3 4 5 6 8 10 12 16	0.902	0.889		
	2.5	2.5	3 4 5 6 8 10 12 16	1.295	1.27		
	3	3	5 6 8 10 12 16 20	1.545	1.52		
	4	4	3 4 5 6 8 10 12 16 20 25 30	2.045	2.02		
	5	5	4 5 6 8 10 12 16 20 25 30 35 40	2.56	2.52		
	6	6	4 5 6 8 10 12 16 20 25 30 35 40 45 50	3.08	3.02	1.5	0.9
	8	8	6 8 10 12 16 20 25 30 35 40 45 50	4.095	4.02	2	1.4
	10	10	8 10 12 16 20 25 30 35 40 45 50	5.095	5.02	2.5	1.9
	12	12	10 12 16 20 25 30 35 40 45 50	6.095	6.02	3	2.4
	16	16	16 20 25 30 35 40 45 50	8.115	8.025	4	3.25

h/θ尺寸表(TAY11/12)

M	2		2.5		3		4		5		6		8		10		12		16	
L	≤2.5	>2.5	≤3	>3	≤3	>3	≤4	>4	≤5	>5	≤6	>6	≤6	>6	≤8	>8	≤12	>12	≤16	>16
h(min)	0.8	1.7	1.2	2	1.2	2	1.5	2.5	2	3	2	3.5	3	5	4	6	4.5	8	6.4	10
θ	60°	45°	60°	45°	60°	45°	60°	45°	60°	45°	60°	45°	60°	45°	60°	45°	60°	45°	60°	45°

平端

代码	型号	M	L	S
TAY01	3	3	3 4 5 6 8 10	1.5
TAY01	4	4	3 4 5 6 8 10	2

TAY01—M4—L10



未税价(元)

优惠价

数量	1~49	50~
价格	100%	另行报价



交货期

3



请按图示订货