
全滚子带内圈型・圆柱型/球面型


双列滚子轴承随动器











◎ 圆柱型D公差:

D	公差		
35~50	0 -0.011		
51~80	0 -0.013		
81~110	0 -0.015		

◎ 球面型 D公差 :-8.05



! 不承诺品牌。

型号			_		_	r	r1	基本额定负载(KN)		最大静态	极限转速	重量	
代码	d		dr	D	В	B ₁	(min)	(min)	Cr(动)	Cor(静)	容许负载 (KN)	(rpm)	(g)
圆柱型 E-BPQ11 球面型 E-BPQ16	15		20	35	10	18 19	0.6	0.3	18.72	18.72 21.84	9.44	3840	100
	15A	0		42	10				10.72 21.04	21.84	3040	160	
	17	-0.008		40	20	21			20.16 24.72	16.24	3360	147	
	17A			47	20	21				₹ 24.12	24.72	3300	222
	20		27	47		25			31.12	39.2	21.76	2880	245
	20A			52	24						39.2		321
	25	0 -0.010	31	52	24				34.48	46.48	24	2304	281
	25A	-0.010		62							46.48		450
	30		38	62	28 29			4	46.56	60.24	28.16	1920	466
	30A			72		1 08	8,	40.30	00.24	60.24	1320	697	
	35		44	72	20	23	EXX		51.12	71.04	45.6	1600	630
	35A			80		14.		51.12	71.04	71.04	1000	840	
	40		49	80		TOMATI			69.2	97.6	60.24	1440	817
	40A	0		90			0.6	0.6			97.6		1130
	45	-0.012	53	85	30	32		0.0	73.2	108	62.96	1280	883
	45A			100	0	02			13.2	100	110.4	1200	1400
	50		58	90				77.	77.04	118.4	65.68	1152	950
	50A		50	110					77.04	110.4	118.4		1690

上表中极限转速数值仅适用润滑脂型号,若采用油润滑的型号极限转速为上述数值的160%左右。



型 된	de	
代码	d	ui
E-BPQ11	(15)	20
E-BPQ16	15A	20







E-BPQ11 — d15



AUTOMATION EXPERT