

交期缩短

Technical drawing of a mechanical part, likely a shaft or axle, showing top and side views with dimensions and labels.

Top View Dimensions:

- Overall length: 255
- Overall width: 62
- Distance from left end to first hole center: 60
- Distance between first and second hole centers: 50
- Distance between second and third hole centers: 30
- Distance between third and fourth hole centers: 40
- Distance between fourth and fifth hole centers: 30
- Distance between fifth and sixth hole centers: 40
- Distance from sixth hole center to right end: 100

Side View Dimensions:

- Overall height: 32
- Distance from top to first hole center: 26
- Distance from top to second hole center: 19
- Distance from top to third hole center: 13

Labels and Features:

- 10-Ø5.5通孔 (10 Ø5.5 through holes)
- 沉孔Ø9.5 (counterbore Ø9.5)
- 8-M4深6 (8 M4 holes, depth 6)
- 右螺纹 (Right thread)
- 左螺纹 (Left thread)
- 进给止动螺钉M5 (Feed stop screw M5)
- Ø8 (8mm diameter hole)

(14)

视角标准：第一视角

Technical drawing of a 4x4 grid of holes. The drawing shows a 4x4 grid of holes with dimensions and labels. The overall width is 90 and the overall height is 40. The distance between the centers of the holes is 40. The distance from the left edge to the center of the first hole is 15. The distance from the top edge to the center of the first hole is 25. The drawing includes labels: "4-Ø4.5通孔" (4 Ø4.5 through holes), "沉孔Ø7.5深4.2" (counter-bore Ø7.5 depth 4.2), and "10-M4深5" (10 M4 depth 5). The drawing is labeled "C向" (View C).

视角标准：第一视角

交货期	5
-----	---

HHN01-40