


代码	类型	组合形式		支柱 材质		表面处理	支座			
		支柱	支座	国标	相当		材质		表面处理	
							国标	相当		
RBX01	对边 法兰型	棒型	RBN01	45	S45C高频淬火	镀硬铬	45	S45C	黑色镀铬	
RBX06					S45C	发黑				
RBX07					0Cr18Ni9	SUS304				
RBX11					45	S45C高频淬火				镀硬铬
RBX16					45	S45C				
RBX21					0Cr18Ni9	SUS304				
RBX26			RBN02		45	S45C		0Cr18Ni9	SUS304	喷细砂无电解镀铬
RBX31					0Cr18Ni9	SUS304	—			
RBX36					45	S45C	发黑			
RBX41					0Cr18Ni9	SUS304	—			
RBX46					45	S45C高频淬火	镀硬铬			
RBX47					45	S45C	发黑			
RBX51		管型	RBN01		0Cr18Ni9	SUS304	—	45	S45C	黑色镀铬
RBX56					45	S45C高频淬火	镀硬铬			
RBX61					0Cr18Ni9	SUS304	—			
RBX66					45	S45C	发黑			
RBX71					0Cr18Ni9	SUS304	—			
RBX76					45	S45C				
RBX01			RBN06		0Cr18Ni9	SUS304	—	0Cr18Ni9	SUS304	—
RBX06					45	S45C				
RBX11					45	S45C高频淬火	镀硬铬			
RBX16					0Cr18Ni9	SUS304	—			
RBX21					45	S45C				
RBX26					0Cr18Ni9	SUS304				
RBX31	棒型	RBN31		45	S45C	—	45	S45C	黑色镀铬	
RBX36				45	S45C					
RBX41				0Cr18Ni9	SUS304	—				
RBX46				45	S45C					
RBX51				0Cr18Ni9	SUS304					
RBX56				45	S45C					
RBX61	管型	RBN32		45	S45C	—	45	S45C	—	
RBX66				45	S45C					
RBX71				0Cr18Ni9	SUS304					
RBX76				45	S45C					
RBX01				0Cr18Ni9	SUS304					
RBX06				45	S45C					


① 如对防锈有要求，请优先选用不锈钢材质或镀铬、喷细砂无电解镍产品。

棒型




通孔型

RBX01/06/07/11/16
RBX21/26/31/36




管型




通孔型

RBX41/46/47/51/56
RBX61/66/71/76




腰孔型

RBX01/06/11/16



腰孔型

RBX21/26



通孔型

型号			L												
代码	D _{g6}	最小单位1	D ₂	W	F	D ₁	H	h	V	K	M	(d)			
组件		6 ^{+0.004 -0.012}	50~160	33	18	23	14	20	6	12.5		—			
棒型	管型	8 ^{+0.005 -0.014}	50~210	38	20	26	16	30	15	4.5	M4	—			
RBX01	RBX41	10 ^{+0.006 -0.017}	50~260	40	22	28	18	35	8	18	5.5	6.0			
RBX06	RBX46	12 ^{+0.006 -0.017}	50~310	46	24	32	20	40	20			10.0			
RBX07	RBX47	15	75~360	56	29	40	25	40	20	6.6	M5	11.7			
RBX11	RBX51	16	75~420	63	34	46	30	45	25			15.2			
RBX16	RBX56	20	75~470	78	41	56	37	50	30	9	M6	16.0			
RBX21	RBX61	25	100~470	82	46	62	42	60							
RBX26	RBX66	30													
RBX31	RBX71														
RBX36	RBX76														

腰孔型

型号		L														
代码	D _{g6}	最小单位	D ₂	W	F	J	K	D ₁	H	h	V	M	(d)			
棒型 管型	6	$\begin{smallmatrix} -0.004 \\ -0.012 \end{smallmatrix}$	50-160	33	18	23			14	20	6	12.5	—			
	8	$\begin{smallmatrix} -0.005 \\ -0.014 \end{smallmatrix}$	50-210	38	20	26	6	4.5	16	30		15	M4			
	10	$\begin{smallmatrix} -0.006 \\ -0.017 \end{smallmatrix}$	50-260	40	22	28			18		35	8	18	6.0		
	12	$\begin{smallmatrix} -0.006 \\ -0.017 \end{smallmatrix}$	50-310	46	24	32										
	15	$\begin{smallmatrix} -0.007 \\ -0.020 \end{smallmatrix}$	75-360	56	29	40			25	40		20		10.0		
	20	$\begin{smallmatrix} -0.007 \\ -0.020 \end{smallmatrix}$	75-420	63	34	46			6.6	30	45		25	M5	11.7	
	25	$\begin{smallmatrix} -0.007 \\ -0.020 \end{smallmatrix}$	75-470	78	41	56	10									
	30	$\begin{smallmatrix} -0.007 \\ -0.020 \end{smallmatrix}$	100-470	82	46	62			9	37	50	10	30	M6	15.2	
									42	60				16.0		

通孔型

型号	代码	D _{g6}	最小单位1	D ₂
RBX01	6	6	50~160	33
RBX06	8	8	50~210	38

RBX06—D8—L150

腰孔型

型号	代码	D _{g6}	最小单位1	D ₂
RBX01	6	6	50~160	33
RBX06	8	8	50~210	38

RBX01—D6—L120



请按图示订货



未税价(元)

数量	1~4	5~
价格	100%	另行报价



交货期

5