

经济型 梯形齿同步带


T5/T10/AT5/AT10型

主体材质：聚氨酯

代码	类型		齿距	材质		颜色 主体	使用温度
				主体	芯线		
ECL11	T5	经济型	5	聚氨酯	钢丝	浅灰色	0~80°C
	T10		10				
	AT5		5				
	AT10		10				

皮带宽度公差

皮带宽度(mm)	公差
3~30	±0.5
31~50	±0.8




代码	齿形	齿距	2α	L	h	H	V
ECL11	T5	5	40°	1.8	1.2	2.4	1.2
	T10	10	40°	3.5	2.5	4.7	2.2
	AT5	5	50°	2.5	1.2	2.7	1.5
	AT10	10	50°	5	2.5	4.5	2

① 适用于轻负载，低转速的传动系统。

② 同步带芯线采用螺旋缠绕的方式排列，分切后可能会看到芯线层，不影响产品性能。

③ 聚氨酯同步带带时间变化可能有颜色差异，对强度及使用性能无影响。



● ECL11-T5(齿距: 5)

型号	皮带公称宽度	皮带周长	齿数
ECL11-T5	100 (10mm)	150	30
		160	32
		165	33
		175	35
		185	37
		200	40
		210	42
		215	43
		220	44
		225	45
		230	46
		245	49
		250	50
		255	51
		260	52
		270	54
		280	56
		295	59
		300	60
		ECL11-T5	150 (15mm)
310	62		
315	63		
320	64		
325	65		
330	66		
340	68		
345	69		
350	70		
355	71		
ECL11-T5	200 (20mm)	360	72
		365	73
		370	74
		375	75
		380	76
		385	77
		390	78
		395	79
		410	82
		420	84
ECL11-T5	250 (25mm)	425	85
		430	86
		435	87
		440	88
		445	89
		450	90
		455	91
		460	92
		470	94
		475	95
ECL11-T5	300 (30mm)	480	96
		500	100
		510	102
		515	103
		525	105
		530	106

● ECL11-T5(齿距: 5)

型号	皮带公称宽度	皮带周长	齿数
ECL11-T5	100 (10mm)	545	109
		550	110
		560	112
		570	114
		575	115
		590	118
		600	120
		610	122
		620	124
		625	125
ECL11-T5	150 (15mm)	630	126
		640	128
		650	130
		660	132
		675	135
		690	138
		700	140
		725	145
		750	150
		760	152
ECL11-T5	200 (20mm)	780	156
		800	160
		815	163
		820	164
		830	166
		840	168
		850	170
		860	172
		885	177
		900	180
ECL11-T5	250 (25mm)	920	184
		940	188
		970	194
		990	198
		1000	200
		1045	209
		1050	210
		1075	215
		1100	220
		1130	226
ECL11-T5	300 (30mm)	1160	232
		1200	240
		1215	243
		1260	252
		1315	263
		1355	271
		1380	276
		1440	288
		1470	294
		1500	300

● ECL11-T10(齿距: 10)

型号	皮带公称宽度	皮带周长	齿数
ECL11-T10	100 (10mm)	300	30
		320	32
		340	34
		350	35
		370	37
		390	39
		400	40
		410	41
		420	42
		440	44
ECL11-T10	150 (15mm)	450	45
		460	46
		470	47
		480	48
		500	50
		510	51
		520	52
		530	53
		550	55
		560	56
ECL11-T10	200 (20mm)	600	60
		610	61
		630	63
		650	65
		660	66
		670	67
		680	68
		690	69
		700	70
		720	72
ECL11-T10	250 (25mm)	730	73
		740	74
		750	75
		760	76
		780	78
		800	80
		810	81
		820	82
		840	84
		850	85
ECL11-T10	300 (30mm)	860	86
		880	88
		890	89
		900	90
		920	92
		950	95
		960	96
		970	97
		980	98
		1000	100
ECL11-T10	400 (40mm)	1010	101
		1020	102
		1050	105
		1080	108
		1100	110
		1110	111
		1140	114
		1150	115
		1210	121
		1240	124
ECL11-T10	500 (50mm)	1250	125
		1260	126
		1300	130
		1390	139
		1460	146
		2050	205

● ECL11-AT5(齿距: 5)

型号	皮带公称宽度	皮带周长	齿数
ECL11-AT5	100 (10mm)	225	45
		255	51
		260	52
		280	56
		300	60
		305	61
		330	66
		340	68
		370	74
		375	75
ECL11-AT5	150 (15mm)	390	78
		420	84
		450	90
		455	91
		460	92
		480	96
		500	100
		525	105
		545	109
		550	110
ECL11-AT5	200 (20mm)	570	114
		600	120
		610	122
		620	124
		630	126
		660	132
		670	134
		710	142
		720	144
		750	150
ECL11-AT5	250 (25mm)	780	156
		825	165
		840	168
		860	172
		900	180
		920	184
		975	195
		990	198
		1020	204
		1030	206
ECL11-AT5	300 (30mm)	1050	210
		1075	215
		1125	225
		1260	252

● ECL11-AT10(齿距: 10)

型号	皮带公称宽度	皮带周长	齿数
ECL11-AT10	150 (15mm)	370	37
		400	40
		500	50
		510	51
		540	54
		550	55
		560	56
		580	58
		600	60
		610	61
ECL11-AT10	200 (20mm)	630	63
		650	65
		660	66
		670	67
		700	70
		730	73
		740	74
		780	78
		800	80
		810	81
ECL11-AT10	250 (25mm)	840	84
		880	88
		890	89
		920	92
		960	96
		980	98
		1000	100
		1010	101
		1050	105
		1080	108
ECL11-AT10	300 (30mm)	1100	110
		1250	125
		1400	140



请按图示订货

代码	型号	皮带公称宽度	皮带周长
ECL11-T5	<100>(10mm)	<160>	
	150(15mm)	165	

ECL11-T5 — 100 — 160



未税价(元)

● 优惠价

数量	1~4	5~
价格	100%	另行报价

