


代码	类型			材质		挂钩相对角度
				国标	相当	
Y-YAUU	中轻载型	半圆形单挂钩	标准型	0Cr18Ni9	SUS304-WPB	180°

① 弹簧两端挂钩保持水平或者垂直状态，无法保证挂钩开口方向每批次都一致，不影响使用。



视角标准：第一视角

型号		线径 d	动态负载时		初始 张力 (N)	弹簧 常数 N/mm
代码	D		最大 位移量 Fmax	最大 载荷 N		
Y-YAUU	2	10	4			0.49
		15	6.7			0.29
		20	10	2.45	0.49	0.2
		25	13.3			0.15
		30	16.7			0.09
	3	15	9.1			0.29
		20	14.3	3.33	0.66	0.19
		25	19.5			0.14
		30	24.8			0.11
		35	30			0.08
Y-YAUU	4	15	7.5			0.51
		20	12.2			0.31
		25	16.9	4.81	0.98	0.23
		30	21.7			0.18
		35	26			0.15
	5	40	30			0.13
		15	5.7			0.89
		20	9.8			0.51
		25	14.2			0.35
		30	18.9	6.37	1.37	0.26
Y-YAUU	6	35	24.3			0.21
		40	28.3			0.18
		45	31.9			0.16
		50	36.4			0.14
		55	40.9			0.12
	8	20	9.6			1.18
		25	14.4			0.78
		30	20.2			0.56
		35	28.8			0.39
		40	30.3	12.94	1.67	0.37
Y-YAUU	10	45	34.8			0.32
		50	41.1			0.27
		55	44.2			0.25
		60	50			0.23
		65	56			0.21
	12	25	10			1.47
		30	14.3			1.03
		35	18.8			0.78
		40	23.8			0.62
		45	28.3	18.63	3.92	0.52
Y-YAUU	14	50	32.6			0.45
		55	37.5			0.39
		60	41.7			0.35
		65	46.9			0.31
		70	50			0.29
	16	30	9.9			1.87
		35	14			1.32
		40	18			1.03
		45	22.2			0.83
		50	26.3			0.71
Y-YAUU	18	55	31.5			0.59
		60	35.7	23.24	4.71	0.52
		65	38.6			0.48
		70	43			0.43
		75	47.3			0.39
	20	80	51			0.36
		90	59			0.31
		100	67.5			0.27

型号		线径 d	动态负载时		初始 张力 (N)	弹簧 常数 N/mm
代码	D		最大 位移量 Fmax	最大 载荷 N		
Y-YAUU	12	35	11.7			3.14
		40	15.5			2.35
		45	19.6			1.86
		50	23.3			1.57
		55	28.7			1.27
	14	60	32.4	47.7	10.49	1.13
		65	37.3			0.98
		70	41.4			0.88
		75	44.9			0.81
		80	49.7			0.74
Y-YAUU	16	90	57.4			0.64
		100	65.4			0.56
		110	73.3			0.5
		120	81.2			0.44
		130	89.1			0.38
	18	40	12.8			3.53
		45	16.7			2.7
		50	21			2.16
		55	25.5			1.77
		60	28.7			1.57
Y-YAUU	20	65	32.8	58.84	13.73	1.37
		70	38.3			1.18
		75	41.8			1.08
		80	46			0.98
		90	54.1			0.83
	22	100	61.3			0.74
		110	68.6			0.64
		120	75.9			0.54
		130	83.2			0.47
		140	90.5			0.4
Y-YAUU	24	45	13.7			3.92
		50	17.7			3.04
		55	22			2.45
		60	26			2.06
		65	30.5			1.77
	26	70	34.3	70.61	16.67	1.57
		75	39.2			1.37
		80	42.3			1.27
		90	50			1.08
		100	57.8			0.93
Y-YAUU	28	125	78.7			0.69
		140	100			0.54

① 初始张力·弹簧常数为参考值。负载(kgf)=负载N×0.101972



请按图示订货

型号		
代码	D	L
Y-YAUU	2	10
Y-YAUU	22	15

Y-YAUU—D2—L10



未税价(元)

● 优惠价

数量	1~19	20~
价格	100%	另行报价