

# 经济型 圆弧齿同步带

## H3M/H5M/H8M型

主体材质：聚氨酯


同步带

F2

代码	类型		齿距	材质		颜色主体	使用温度
				主体	芯线		
ECL11	H3M	经济型	3	聚氨酯	钢丝	浅灰色	0~80°C
	H5M		5				
	H8M		8				

皮带宽度公差

皮带宽度(mm)	公差
3~30	±0.5
31~50	±0.8



代码	齿形	齿距	h	H	PLD	R <sub>1</sub>	R <sub>2</sub>
ECL11	H3M	3	1.17	2.4	0.381	0.86	0.3
	H5M	5	2.06	3.8	0.572	1.5	0.41
	H8M	8	3.38	6	0.686	2.59	0.76

- ① 适用于轻负载，低转速的传动系统。
- ② 同步带芯线采用螺旋缠绕的方式排列，分切后可能会看到芯线层，不影响产品性能。
- ③ 聚氨酯同步带随时间变化可能有颜色差异，对强度及使用性能无影响。



● ECL11-H3M(齿距: 3)

● ECL11-H3M(齿距: 3)

● ECL11-H5M(齿距: 5)

● ECL11-H5M(齿距: 5)

● ECL11-H8M(齿距: 8)

ECL11-H3M(齿距: 3)				ECL11-H3M(齿距: 3)				ECL11-H5M(齿距: 5)				ECL11-H5M(齿距: 5)				ECL11-H8M(齿距: 8)			
型号	皮带公称宽度	皮带周长	齿数	型号	皮带公称宽度	皮带周长	齿数	型号	皮带公称宽度	皮带周长	齿数	型号	皮带公称宽度	皮带周长	齿数	型号	皮带公称宽度	皮带周长	齿数
ECL11-H3M	60 (6mm)	138	46	ECL11-H3M	60 (6mm)	477	159	ECL11-H5M	90 (9mm)	160	32	ECL11-H5M	90 (9mm)	585	117	ECL11-H8M	200 (20mm)	344	43
		150	50			480	160			225	45			590	118			352	44
		177	59			486	162			230	46			595	119			376	47
		186	62			489	163			235	47			600	120			384	48
		201	67			492	164			240	48			605	121			400	50
		210	70			495	165			245	49			610	122			416	52
		219	73			501	167			250	50			615	123			424	53
		234	78			513	171			255	51			625	125			432	54
		240	80			516	172			260	52			630	126			440	55
		249	83			519	173			265	53			635	127			448	56
		255	85			522	174			270	54			640	128			464	58
		258	86			525	175			275	55			645	129			472	59
	264	88	531		177	285	57		650	130	480		60						
	270	90	534		178	290	58		655	131	488		61						
	288	96	537		179	295	59		665	133	496		62						
	291	97	540		180	300	60		670	134	512		64						
	297	99	546		182	305	61		675	135	520		65						
	300	100	549		183	330	66		680	136	528		66						
	306	102	552		184	335	67		685	137	536		67						
	309	103	558		186	340	68		690	138	544		68						
	312	104	564		188	360	72		700	140	552		69						
	318	106	570		190	365	73		710	142	560		70						
	321	107	576		192	370	74		715	143	568		71						
	324	108	582		194	375	75		720	144	576		72						
	330	110	588		196	380	76		725	145	584		73						
	336	112	591		197	390	78		730	146	592		74						
	339	113	594		198	395	79		740	148	600		75						
	345	115	597		199	400	80		745	149	608		76						
351	117	600	200	405	81	750	150	616	77										
354	118	603	201	410	82	755	151	624	78										
357	119	606	202	420	84	760	152	632	79										
360	120	633	211	425	85	765	153	640	80										
363	121	648	216	430	86	770	154	648	81										
366	122	654	218	435	87	775	155	672	84										
372	124	669	223	440	88	780	156	680	85										
375	125	672	224	450	90	820	164	688	86										
381	127	675	225	460	92	830	166	696	87										
384	128	681	227	465	93	865	173	712	89										
390	130	684	228	470	94	870	174	720	90										
399	133	687	229	480	96	880	176	736	92										
405	135	699	233	490	98	890	178	744	93										
411	137	708	236	500	100	900	180	768	96										
414	138	711	237	505	101	910	182	776	97										
420	140	720	240	510	102	920	184	856	107										
426	142	726	242	520	104	930	186	920	115										
432	144	732	244	525	105	940	188	960	120										
438	146	741	247	535	107														
444	148	744	248	540	108														
447	149	750	250	545	109														
453	151	765	255	550	110														
459	153	855	285	560	112														
462	154	1050	350	565	113														
474	158			570	114														
				575	115														
				580	116														



型号		
代码	皮带公称宽度	皮带周长
ECL11-H3M	60(6mm)	438
ECL11-H3M	90(9mm)	450

ECL11-H3M—60—138



优惠价	
数量	价格
1~4	100%
5~	另行报价

