


除尘风管配件

直接头/弯头/大小头

直接头


代码	类型	材质	使用温度范围
BMG52	直接头 标准型	SUS304	0~160℃



视角标准：第一视角

45°弯头

代码	类型	材质	使用温度范围
BMG53	45°弯头 标准型	SUS304	0~160℃



视角标准：第一视角


型号	公称直径	L	D	t
BMG52	38	60	38	1.2
	50		50	1.5
	65		63.5	
	75		76	
	100	80	102	2
	113		112	
	125		124	
	150		152	

型号	公称直径	D	A1	A2	A3	t
BMG53	38	38	28	41	69	1.2
	50	50		50	86.5	1.5
	65	63.5	35	52.5	91	
	75	76		56	95	
	100	102	45	73	122	2
	113	112	50	81.5	139	
	125	124	55	89	151.5	
	150	152	60	98	170	




90°弯头

代码	类型	材质	使用温度范围
BMG54	90°弯头	SUS304	0~160℃
BMG55			

标准型
BMG54



法兰型
BMG55




视角标准：第一视角

型号	公称直径	D1	A	A1	B	t	法兰尺寸		
标准型 BMG54	38	38	61	28	63	1.2	66	52	6.6
	50	50	78		82	1.5	79	65	
	65	63.5	90	35	89		91.5	77.5	
	75	76	100		94		111	94	9
	100	102	130	45	124	2	136	119	
法兰型 BMG55	113	112	138	50	140		152	134	
	125	124	149	55	151		168	148	
	150	152	174	60	176		193	173	



大小头

代码	类型	材质	使用温度范围
BMG69	大小头	SUS304	0~160℃
BMG70			

标准型
BMG69



法兰型
BMG70



视角标准：第一视角

型号	公称直径	软管适用公称直径	D1	D2	L	t1	t2	法兰尺寸		
标准型 BMG69	38	50	38	50	90	1.2	1.5	79	65	6.6
	50	65	50	63.5		1.5		91.5	77.5	
	65	75	49	76				111	94	
	75	100	50	102	100			136	119	
	100	75	63.5	76		2	2	111	94	
法兰型 BMG70	113	100		98				136	119	
	125	113	102	112				152	134	
	150	125	112	124				168	148	
		150	124	152				193	173	



请按图订货



未税价(元)

直接头

代码	公称直径
BMG52	38
	50

BMG52—50

数量	1~4	5~
价格	100%	另行报价

未税价(元)

大小头

代码	公称直径	软管适用公称直径
BMG69	38	50
	50	65

BMG69—38—50



交货期

11