

标准型 圆法兰型

● 特点

- 自润滑、免维护，适用于中轻载、低速运动；
- 适用于直线、旋转运动。

! 与本产品相配轴径公差：d8重载、e7轻载、g6高精度(仅供参考)。




! 与本产品相配固定座直径公差：H7(仅供参考)。

! 产品压入座孔时在座孔端部或者内壁涂抹少许润滑油，利用压机或台钳将其慢慢压入座孔，请勿用力敲击产品，以免引起产品变形。





$d=6 \sim 13$

$d=16 \sim 50$



$d=6 \sim 12$


$d=16 \sim 30$



视角标准：第一视角

型号			L	D _{h7}	H	T	h	d ₁	d ₂	P.C.D	短头内六角螺栓 (需另行购买)
代码	d _{F7}										
E-OCR01	6	+0.022 +0.010	10 15 20 25	10	⁰ -0.015	25					17
	8	+0.028 +0.013	15 20 25 30	12		27	4	2.3	3.3	6	19
	10		15 20 25 30	14	⁰ -0.018	29					21
	12		20 25 30 35	18		36					26
	13	+0.034 +0.016	20 25 30 35 40	19		37	5	3	4.3	7.5	27
	16		20 25 30 35 40 50	22	⁰ -0.021	40					30
	20		20 25 30 35 40 50 60	28		49					38
	25	+0.041 +0.020	25 30 35 40 50 60 70	33		54	6	3.7	5.3	9	43
	30		30 35 40 50 60 70	38		63					50
	35		40 50 60 70 80	44	⁰ -0.025	69	8	4.3	6.3	11	56
	40	+0.050 +0.025	40 60 70 80 100	50		82					66
	50		50 60 70 80 100	62	⁰ -0.030	94	10	5.3	8.5	14	78

型号		L		D _{h7}		H		T		h		d ₁		d ₂		P.C.D		短头内六角螺栓 (需另行购买)		
代码	d _{F7}																			
E-OCG61	6	+0.022 -0.010	15 20		10	0 -0.015	25													
	8		15	20 25 30	12		27	4	2.3	3.3	6	17	M3×10(2个)							
	10	+0.028 -0.013	20	25 30 35	14	0 -0.018	29					21								
	12	+0.034 -0.016	20	25 30 35 40	18		36					26	M4×12(2个)							
	16		25 30 35 40 50	22		40	5	3	4.3	7.5	30	M4×12(4个)								
	20	25 30 35 40 50 60	28	0 -0.021	49						38	M5×16(4个)								
	25	+0.041 -0.020	30 35 40 50 60 70	33		54	6	3.7	5.3	9	43									
	30		30 35 40 50 60 70	38	0 -0.025	63	8	4.3	6.3	11	50	M6×20(4个)								



请按图示订货

E-OCG61—d6—L15

未税价(元) E-OCR01

	● 优惠价	
	数量	1~49 50~
	价格	100% 另行报价

未税价(元) E-OCR01

	● 优惠价	
	数量	1~9 10~
	价格	100% 另行报价

未税价(元)  E-OCG61

 E-OCR01



 E-OCG61