


代码	类型	D公差	材质		硬度	表面处理
			国标	相当		
SAD01	标准型	g6	GCr15	SUJ2	高频淬火	镀硬铬, 镀层硬度HV850~, 镀层厚度3~5μm
SAD02					有效硬化层深度见P15	—
SAD06			9Cr18Mo	SUS440C	淬火热处理	—
SAD07					GCr15 HRC56~	镀硬铬, 镀层硬度HV850~, 镀层厚度3~5μm
SAD21			45	S45C	S45C HRC56~	—
SAD22					9Cr18Mo HRC54~	镀硬铬, 镀层硬度HV850~, 镀层厚度3~5μm



① 圆度/直线度/垂直度/同轴度/硬度变化/铬层分布, 请参阅导向轴产品简介。



型号			L 最小单位1	C
代码	Dg6			
SAD01	3	-0.002 -0.008	8~400	0.2
	4			
	5	-0.004 -0.012		
	6			
	8	-0.005 -0.014		
SAD02	10		15~800	0.5
SAD06	12		15~1000	
SAD07	13		20~1000	
SAD21	15	-0.006 -0.017	25~1200	
SAD22	16		30~1200	
	18		30~1500	1.0
	20		40~1500	
	25	-0.007 -0.020	60~1500	
	30			
	35			
	40	-0.009 -0.025		
	50			



型号			
代码	D	L	C
SAD01	3	8~400	0.2
SAD02	4		

SAD01—D3—L12

① 可选加工

型号			
代码	D	L	可选加工代码
SAD01	3	8~400	LC EC()
SAD02	4		6C() JD()...

SAD01—D3—L12—SC4







优惠价	
数量	1~9 10~
价格	100% 另行报价



3



代码	技术说明																																															
LC	变更L尺寸公差	选型方法 LC ① 最小单位0.1 ② L < 300变更为$L_{\pm 0.03}$; 300≤L < 600变更为$L_{\pm 0.05}$; L≥600变更为$L_{\pm 0.1}$																																														
																																																
EC()	增加1个平面	选型方法 EC10-K8 ① 最小单位1 <table><tr><th>D</th><th>h</th></tr><tr><td>3~5</td><td>0.5</td></tr><tr><td>6~18</td><td>1</td></tr><tr><td>20~40</td><td>2</td></tr><tr><td>50</td><td>3</td></tr></table>		D	h	3~5	0.5	6~18	1	20~40	2	50	3																																			
	D	h																																														
3~5	0.5																																															
6~18	1																																															
20~40	2																																															
50	3																																															
ED()	增加2个平面	选型方法 ED10-K8-T20 ① 最小单位1 <table><tr><th>D</th><th>h</th></tr><tr><td>3~5</td><td>0.5</td></tr><tr><td>6~18</td><td>1</td></tr><tr><td>20~40</td><td>2</td></tr><tr><td>50</td><td>3</td></tr></table>		D	h	3~5	0.5	6~18	1	20~40	2	50	3																																			
	D	h																																														
3~5	0.5																																															
6~18	1																																															
20~40	2																																															
50	3																																															
SC()	增加1处扳手槽	选型方法 SC5 ① 最小单位1 ② 适用于D5以上规格 <table><tr><th>D</th><th>W</th><th>V</th></tr><tr><td>6</td><td>5</td><td></td></tr><tr><td>8</td><td>7</td><td>6</td></tr><tr><td>10</td><td>8</td><td></td></tr><tr><td>12</td><td>10</td><td></td></tr><tr><td>13</td><td>11</td><td></td></tr><tr><td>15</td><td>13</td><td></td></tr><tr><td>16</td><td>14</td><td>11</td></tr><tr><td>18</td><td>16</td><td></td></tr><tr><td>20</td><td>17</td><td></td></tr><tr><td>25</td><td>22</td><td></td></tr><tr><td>30</td><td>27</td><td>16</td></tr><tr><td>35</td><td>30</td><td></td></tr><tr><td>40</td><td>36</td><td></td></tr><tr><td>50</td><td>41</td><td>21</td></tr></table>		D	W	V	6	5		8	7	6	10	8		12	10		13	11		15	13		16	14	11	18	16		20	17		25	22		30	27	16	35	30		40	36		50	41	21
	D	W	V																																													
6	5																																															
8	7	6																																														
10	8																																															
12	10																																															
13	11																																															
15	13																																															
16	14	11																																														
18	16																																															
20	17																																															
25	22																																															
30	27	16																																														
35	30																																															
40	36																																															
50	41	21																																														
																																																

代码	技术说明													
JD ()	增加1个键槽 	选型方法 JD10-J10 ① 最小单位1 ② JD=0时, 见右图 ③ D12, D16, D20, D25, D30适用于此可选加工 ④ 带键槽导向轴支座参阅P79。 ⑤ 键槽详情参阅P15。												
VD ()	增加V形槽 	选型方法 VD8 ① 最小单位1 ② 适用于D5以上规格 <table><thead><tr><th>D</th><th>W</th></tr></thead><tbody><tr><td>6-8</td><td>2</td></tr><tr><td>10-18</td><td>4</td></tr><tr><td>20-25</td><td>6</td></tr><tr><td>30-35</td><td>8</td></tr><tr><td>40-50</td><td>12</td></tr></tbody></table>	D	W	6-8	2	10-18	4	20-25	6	30-35	8	40-50	12
D	W													
6-8	2													
10-18	4													
20-25	6													
30-35	8													
40-50	12													
VE ()	增加两端V形槽 	选型方法 VE180-G8 ① 最小单位1 ② 适用于D5以上规格 <table><thead><tr><th>D</th><th>W</th></tr></thead><tbody><tr><td>6-8</td><td>2</td></tr><tr><td>10-18</td><td>4</td></tr><tr><td>20-25</td><td>6</td></tr><tr><td>30-35</td><td>8</td></tr><tr><td>40-50</td><td>12</td></tr></tbody></table>	D	W	6-8	2	10-18	4	20-25	6	30-35	8	40-50	12
D	W													
6-8	2													
10-18	4													
20-25	6													
30-35	8													
40-50	12													

① 选择2个或以上可选加工时, 各加工部位间隔2mm以上。

② 可选加工可能会使产品硬度降低。