

# 圆型 · P尺寸选择型/P.L.B尺寸指定型 大头锥角型


## 定位销

P尺寸选择型			P.L.B尺寸指定型			材质		硬度	表面处理
Dm6	Dp6	Dg6	Dm6	Dp6	Dg6	国标	相当		
YBP01	YBP11	—	YBP41	YBP51	YBP61	9CrWmN	SKS3	淬火硬度58~61HRC	—
YBP02	YBP12	—	YBP42	YBP52	YBP62	9CrWmN	SKS3	淬火硬度58~61HRC, 镀层硬度850HV~	镀硬铬, 镀层厚度3~5μm
YBP03	YBP13	—	YBP43	YBP53	YBP63	—	—	—	—
YBP05	YBP15	—	YBP45	YBP55	YBP65	0Cr18Ni9	SUS304	—	—
YBP06	YBP16	—	YBP46	YBP56	YBP66	0Cr18Ni9	SUS304	—	—
YBP08	YBP18	—	YBP48	YBP58	YBP68	9Cr18Mo	SUS440C	—	—
—	—	YBP20	—	—	—	GCr15	SUJ2	淬火硬度HRC56~	镀层硬度850HV~ 镀硬铬, 镀层厚度3~5μm




### P尺寸选择型

YBP01/02/03/05/06/08  
YBP11/12/13/15/16/18




### P尺寸选择型

YBP20



### P.L.B尺寸指定型

YBP41/42/43/45/46/48  
YBP51/52/53/55/56/58  
YBP61/62/63/65/66/68



### P尺寸公差表

P	g6
3	-0.002 -0.008
4~6	-0.004 -0.012
8~10	-0.005 -0.014
13~16	-0.006 -0.017
20~30	-0.007 -0.020

视角标准：第一视角

① SUS440C材质的D部加工有识别槽。

### ② P尺寸选择型

型号		D公差			P			L	B	C	E	V
代码	D	m6	p6	g6	2	3 4	4	3	0.1	0.5	0	
Dm6 Dp6 YBP01 YBP11 YBP02 YBP12 YBP03 YBP13 YBP05 YBP15 YBP06 YBP16 YBP08 YBP18	1	+0.008	+0.012	-0.002	2	3 4	3	3	0.1	0.5	0	
	2	+0.002	+0.006	-0.008	3 4	4 5 6	4	5	0.5	1	2	
	3	—	—	—	4 5 6	5 6	5	6	1	3	—	
	4	+0.012	+0.020	-0.004	5 6	6 8	6	8	1.5	—	—	
	5	+0.004	+0.012	-0.012	6 8	8 10	10	8	—	—	1	
	6	—	—	—	8 10	10 12 13	15	10	2	4	—	
	8	+0.015	+0.024	-0.005	10 12 13	12 13 15	15	10	—	—	—	
	10	+0.006	+0.015	-0.014	12 13 15	13 15 16	—	—	—	—	—	
	12	+0.018	+0.029	-0.006	13 15 16	15 16	—	—	—	—	—	
	13	+0.007	+0.018	-0.017	15 16	16 20 25	22	10	3	5	2	
Dg6 YBP20	16	+0.021	+0.035	-0.007	16 20 25	25 30	30	15	—	—	—	
	20	+0.008	+0.022	-0.020	25 30	—	—	—	—	—	—	

### ③ P.L.B尺寸指定型

型号		D公差			最小单位0.01	最小单位1	最小单位0.1	C	E	V
代码	D	m6	p6	g6	P	L	B	—	—	—
Dm6 Dp6 Dg6 YBP41 YBP51 YBP61 YBP42 YBP52 YBP62 YBP43 YBP53 YBP63 YBP45 YBP55 YBP65 YBP46 YBP56 YBP66 YBP48 YBP58 YBP68	1	+0.008	+0.012	-0.002	1.20~3.00	2~3	1.0~5.0	0.1	0.5	0
	2	+0.002	+0.006	-0.008	2.50~8.00	2~8	—	0.5	1	—
	3	—	—	—	3.50~10.00	3~10	—	—	2	—
	4	—	—	—	4.50~10.00	3~15	1.0~15.0	—	—	—
	5	+0.012	+0.020	-0.004	5.50~12.00	5~15	—	1	3	—
	6	+0.004	+0.012	-0.012	6.50~12.00	5~15	1.0~30.0	—	—	1
	8	+0.015	+0.024	-0.005	8.50~16.00	5~20	—	1.5	—	—
	10	+0.006	+0.015	-0.014	11.00~18.00	5~25	—	—	4	—
	12	—	—	—	13.00~20.00	6~30	3.0~30.0	—	—	—
	13	+0.018	+0.029	-0.006	14.00~20.00	7~30	—	2	—	—
16	+0.007	+0.018	-0.017	17.00~30.00	8~35	5.0~30.0	—	—	—	
20	+0.021	+0.035	-0.007	22.00~30.00	10~45	—	3	5	2	



可选加工

**代码** 变更E尺寸

**技术说明**

**选型方法 EC2**

① 最小单位1

② 圆锥小头直径1min;

③ B尺寸因EC的变化而变化

D	EC	D	EC
2	2~5	8	5~16
3	3~9	10	—
4	4~11	12	5~22
5	—	13	—
6	4~13	16	6~23
—	—	20	—

**代码** 增加内螺纹

**技术说明**

**选型方法 MA**

D	MA	V1
6	M3	4
8~13	M4	6
16~20	M6	9

**代码** 变更颈部退刀槽为R0.5

**技术说明**

**选型方法 RC**

① P-D≤2不适用

### ④ P尺寸选择型

型号	D公差			P
代码	D	m6	p6	g6
YBP01	2	+0.008	+0.012	-0.002
YBP02	3	+0.002	+0.006	-0.008

### ⑤ 可选加工 (P尺寸选择型)

型号	D公差			P	可选加工代码
代码	D	m6	p6	g6	(EC) MA (RC)
YBP01	2	+0.008	+0.012	-0.002	3 4
YBP02	3	+0.002	+0.006	-0.008	4 5 6

**交货期** 3

① 无表面处理/无硬度

**交货期** 5

② 无表面处理

**交货期** 6

③ 有表面处理

### ⑥ P.L.B尺寸指定型

型号	D公差			最小单位0.01	最小单位1	最小单位0.1
代码	D	m6	g6	P	L	B
YBP41	2	+0.008	+0.012	-0.002	2.50~3.00	3~9
YBP42	3	+0.002	+0.006	-0.008	3.50~10.00	3~10

YBP41—D2—P4—L5—B5

**优惠价**

数量 1~4 5~

价格 100% 另行报价

未税价(元)

请按图示订货