



# 定位销

## 圆型·P尺寸指定型 小头锥角型

P尺寸指定型		材质		硬度	表面处理
Dm6	Dp6	国标	相当		
YCR21	YCR31	9CrWMn	SKS3	淬火硬度58~61HRC	—
YCR22	YCR32			淬火硬度58~61HRC, 镀层硬度850HV~	镀硬铬, 镀层厚度3~5μm
YCR23	YCR33			—	—
YCR25	YCR35	0Cr18Ni9	SUS304	—	—
YCR26	YCR36			镀层硬度850HV~	镀硬铬, 镀层厚度5~8μm
YCR28	YCR38	9Cr18Mo	SUS440C	淬火硬度48~53HRC	—



a=0.4(P≤2)  
a=0.8(P≥3)  
d=0.05(P≤2)  
d=0.1(P≥3)



视角标准：第一视角

代码	型号	D公差		最小单位0.01	L	B	C	E	V	
		D	m6							p6
Dm6	Dp6	2	+0.008	+0.012	1.00~2.00	4	2	0.3	0.5	0
		3	+0.002	+0.006	1.00~3.00	5	3	0.5		
		4			2.00~4.00	10	5	1	1	1
		5	+0.012	+0.020	2.00~5.00	15	6	1.5		
		6	+0.004	+0.012	2.00~6.00	22	8	2	2	
		8	+0.015	+0.024	3.00~8.00	30	10	3		
		10	+0.006	+0.015	3.00~10.00				3	
		12	+0.018	+0.029	5.00~12.00					
		13	+0.007	+0.018	6.00~13.00				4	
		16	+0.021	+0.035	10.00~16.00					
20	+0.008	+0.022	13.00~20.00							



请按图示订货

型号	D公差		P
代码	D	m6	p6
YCR21	+0.008	+0.012	1.00~2.00
YCR22	+0.002	+0.006	1.00~3.00

YCR21—D2—P2

可选加工

型号	D公差		P	可选加工码
代码	D	m6	p6	
YCR21	+0.008	+0.012	1.00~2.00	RC
YCR22	+0.002	+0.006	1.00~3.00	RC

YCR21—D2—P2—EC1



优惠价

数量	1~4	5~
价格	100%	另行报价

未税价(元)



交货期

8



可选加工

代码	技术说明	
RC	变更颈部退刀槽为R0.5	选型方法 RC ① D-P < 2 不适用

代码	技术说明																												
EC()	变更前端锥角部长度 变更E尺寸	选型方法 EC4 ① 最小单位1 ② 圆锥小头直径1min ③ B尺寸因EC的变化而变化																											
		<table border="1"> <thead> <tr> <th>D</th> <th>EC</th> <th>D</th> <th>EC</th> </tr> </thead> <tbody> <tr> <td>2</td> <td>1</td> <td>8</td> <td>4-13</td> </tr> <tr> <td>3</td> <td>1-3</td> <td>10</td> <td>4-16</td> </tr> <tr> <td>4</td> <td>2-5</td> <td>12</td> <td>4-20</td> </tr> <tr> <td>5</td> <td>3-7</td> <td>13</td> <td>4-21</td> </tr> <tr> <td>6</td> <td>3-9</td> <td>16</td> <td>4-22</td> </tr> <tr> <td>20</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	D	EC	D	EC	2	1	8	4-13	3	1-3	10	4-16	4	2-5	12	4-20	5	3-7	13	4-21	6	3-9	16	4-22	20		
D	EC	D	EC																										
2	1	8	4-13																										
3	1-3	10	4-16																										
4	2-5	12	4-20																										
5	3-7	13	4-21																										
6	3-9	16	4-22																										
20																													

定位销  
夹具用衬套

A6

