



焊接桁架



代码	类型	材质		表面处理
		固定板	立柱	
ZGH30	顶部安装型	A3	Q235	烤漆
ZGH31	侧面安装型			
ZGH32	悬臂安装型			






顶部安装型
ZGH30



侧面安装型
ZGH31



悬臂安装型
ZGH32



视角标准：第一视角

顶部安装型/侧面安装型

型号	G	H 最小单位5	T	颜色	W	W ₁	T ₁	d	B	B ₁	F	H ₁
顶部安装型 ZGH30	50	300~600	10	N(RAL7035工业灰) W(RAL9016交通白)	120	90	10	11	120	76	H-70	—
	80	300~800	12		150	110	12	13	150	96		
侧面安装型 ZGH31	50	300~600	10	N(RAL7035工业灰) W(RAL9016交通白)	120	90	10	11	—	32	H-80	H-80
	80	400~800	15		150	110	12	13	—	50		

悬臂安装型

型号	G	H 最小单位5	T	B	适用单轴机器人 有效行程	颜色	S	S ₁	W	W ₁	T ₁	d	M	B ₁	B ₂	F	L ₁	L ₂	适用单轴 机器人代码*
ZGH32	50	300~600	12	80	100 150 200 250	N(RAL7035工业灰)	160	120	120	80	10	11	M4	72	23	—	73	40	YBSC6
	80		15	102	100 150 200	W(RAL9016交通白)	180	140	140	100	12	13	M5	92	82	H-70	86	200	YBSC10/YBSR10
				135									M6	125	106		19		YBSR14

① *仅适用电机安装方式为BC(电机直连)的产品。

N、N₁、L、L₃尺寸表

适用单轴 机器人代码	适用单轴机器人 有效行程	N	N ₁	L	L ₃
YBSC6	100	12	5	308	—
	150	14	6	358	
	200	16	7	408	
YBSC10 YBSR10	250	18	8	458	50
	100	4		350	
	150			400	
YBSR14	200	6	1	450	100
	100			350	
	150			400	
	200			450	150

悬臂安装型

型号	G	H 最小单位5	T	B	适用单轴机器人 有效行程	颜色
ZGH32	50	300~600	12	80	100 150 200 250	N(RAL7035工业灰)
	80		15	102	100 150 200	W(RAL9016交通白)

请按图示订货

ZGH32 — G50 — H300 — T15 — B102 — 200 — W

优惠价


数量	1~9	10~
价格	100%	另行报价




未税价(元)



顶部安装型



侧面安装型



悬臂安装型

