


代码	类型	材质		硬度
		国标	相当	
UEN21	垫片环	0Cr18Ni9	SUS304H	350~400HV
UEN26		H62	黄铜(C2801P或C2680P)	—

① 由于工艺及批次问题, 小部分产品背面边缘处有0.1~1mm缺口。



T公差表

代码	T公差								
	0.01	0.02	0.03	0.05	0.1	0.2	0.3	0.5	1.0
UEN21	±0.003	±0.003	±0.005	±0.005	±0.02	±0.03	±0.035	±0.04	±0.05
UEN26	—	—	—	±0.005	±0.02	±0.03	±0.04	±0.05	±0.08



型号	d	D	T
UEN21	2	3	(0.01) (0.02) (0.03) 仅UEN21 (0.05) 仅UEN21/UEN26 0.1 0.2 0.3 0.5 1.0
	3	4	
	4	5 6 7 8 9 10	
	5	6 7 8 9 10 12 13	
	6	7 8 9 10 12 13 14 15 16	
	8	8 9 10 12 13 14 15 16 18 20	
	10	10 12 13 14 15 16 18 20	
	12	12 13 14 15 16 18 20	
	15	15 16 18 20 21 22	
	16	18 20 21 22 24	
	17	20 21 22 24 28	
	20	20 21 22 24 28 30 32	
	22	24 28 30 32 35 40	
	25	28 30 32 35 40	
	28	30 32 35 40 42	
	30	32 35 40 42 45	
	35	35 40 42 45 50	
40	42 45 50 55		
45	45 50 55		
45	50 55		

① 当d=2, D=3时, 厚度T0.5、T1.0不适用UEN21。

① 当d=3, D=4时, 厚度T0.5、T1.0不适用UEN21。



请按图示订货

型号			
代码	d	D	T
UEN21	2	3	0.1
	2	4 5 6	0.2

UEN21 — d2 — D4 — T0.2



未税价(元)

优惠价

数量	1~9	10~
价格	100%	另行报价



交货期

5