

内六角紧定螺钉

平端/锥端/凹端/凸端




视角标准：第一视角

代码				螺纹	材质		硬度	表面处理
平端	锥端	凹端	凸端		国标	相当		
TAY01	TAY11	TAY21	TAY31	粗牙	ML40Cr		45HRC~	发黑
TAY02	TAY12	TAY22	TAY32		0Cr18Ni9 SUS304		—	


※当M与L相等时，
锥端(TAY11、TAY12)
尾部角度为60°。

平端
TAY01/02




① 适用标准：DIN 913-1980

锥端
TAY11/12




① 适用标准：DIN 914-1980

凹端
TAY21/22



① 适用标准：DIN 916-1980

凸端
TAY31/32



① 适用标准：DIN 915-1980

■ 平端(ML40Cr)

型号	M	L	S	h	d
代码	M	L	S	h	d
2	2 3 4 5		0.9	0.8	1
2.5	3 4 5 6 8		1.3	1.2	1.5
3	3 4 5 6 8 10 12 16 20		1.5	1.2	2
4	3 4 5 6 8 10 12 16 20		2	1.5	2.5
5	4 5 6 8 10 12 16 20 25 30		2.5	2	3.5
6	5 6 8 10 12 16 20 25 30 35 40 45 50		3	2	4
8	6 8 10 12 16 20 25 30 35 40 45 50		4	3	5.5
10	8 10 12 16 20 25 30 35 40 45 50		5	4	7
12	10 12 16 20 25 30 35 40 45 50 60 70		6	4.8	8
16	16 20 25 30 35 40 45 50 60 70		8	6.4	12

■ 锥端(ML40Cr)

型号	M	L	S	h	d
代码	M	L	S	h	d
3	3 4 5 6 8 10 12 20		1.5	1.2	1
4	4 5 6 8 10 12 16		2	1.5	—
5	5 6 8 10 12 16 20		2.5	2	—
6	6 8 10 12 16 20 25 30 35 40		3	2	1.5
8	8 10 12 16 20 25 30		4	3	2
10	10 12 16 20 25 30		5	4	2.5
12	12 16 20 25 30 35 40		6	4.8	3
16	16 20 25 30 35 40 45 50		8	6.4	3.5

■ 平端(SUS304)

型号	M	L	S	h	d
代码	M	L	S	h	d
2	2 3 4 5 6 8 10 12		0.8	0.8	1
2.5	2.5 3 4 5 6 8 10 12		1.2	1.2	1
3	3 4 5 6 8 10 12 16 20 25		1.5	1.2	2
4	3 4 5 6 8 10 12 16 20 25 30 35 40		2	1.5	2.5
5	3 4 5 6 8 10 12 16 20 25 30 35 40		2.5	2	3.5
6	4 5 6 8 10 12 16 20 25 30 35 40 45 50		3	2	4
8	5 6 8 10 12 16 20 25 30 35 40 45 50 60		4	3	5.5
10	6 8 10 12 16 20 25 30 35 40 45 50 55 60		5	4	7
12	8 10 12 16 20 25 30 35 40 45 50 55		6	4.8	8
16	12 16 20 25 30 35 40 45 50		8	6.4	12

■ 锥端(SUS304)

型号	M	L	S	h	d
代码	M	L	S	h	d
2	3 4 5 6 8 10 12 16		0.9	0.8	—
2.5	3 4 5 6 8 10 12 16		1.3	1.2	—
3	3 5 6 8 10 12 16 20		1.5	1.2	—
4	3 4 5 6 8 10 12 16 20 25 30		2	1.5	—
5	4 5 6 8 10 12 16 20 25 30 35 40		2.5	2	—
6	4 5 6 8 10 12 16 20 25 30 35 40 45 50		3	2	1.5
8	6 8 10 12 16 20 25 30 35 40 45 50		4	3	2
10	8 10 12 16 20 25 30 35 40 45 50		5	4	2.5
12	10 12 16 20 25 30 35 40 45 50		6	4.8	3
16	12 16 20 25 30 35 40 45 50		8	6.4	3.5

■ 凹端(ML40Cr)

型号	M	L	S	h	d
代码	M	L	S	h	d
3	3 4 5 6 8 10 12 16 20		1.5	1.2	1.4
4	3 4 5 6 8 10 12 16 20 25		2	1.5	2
5	4 5 6 8 10 12 16 20 25 30 35 40 45 50		2.5	2	2.5
6	5 6 8 10 12 16 20 25 30 35 40 45 50 55 60 70		3	2	3
8	6 8 10 12 16 20 25 30 35 40 45 50 55 60 65 70		4	3	5.5
10	8 10 12 16 20 25 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100		5	4	6
12	10 12 16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100		6	4.8	8
14	14 16 20 25 30 35 40 45 50 55 60 65		6	5.6	9
16	16 20 25 30 35 40 45 50 55 60 65 70 75 80 90 100		8	6.4	10
20	20 25 30 35 40 45 50 55 60 65 70 75 80 90 100		10	7.2	12

■ 凹端(SUS304)

型号	M	L	S	h	d
代码	M	L	S	h	d
2	2 3 4 5 6 8 10 12		0.9	0.8	1
2.5	2.5 3 4 5 6 8		1.3	1.2	1.2
3	3 4 5 6 8 10 12 16 20 25		1.5	1.2	1.4
4	3 4 5 6 8 10 12 16 20 25 30		2	1.5	2
5	3 4 5 6 8 10 12 16 20 25 30 35 40		2.5	2	2.5
6	4 5 6 8 10 12 16 20 25 30 35 40 45 50		3	2	3
8	5 6 8 10 12 16 20 25 30 35 40 45 50		4	3	5
10	6 8 10 12 16 20 25 30 35 40 45 50		5	4	6
12	8 10 12 16 20 25 30 35 40 45 50 55		6	4.8	8
16	12 16 20 25 30 35 40 45 50		8	6.4	10

■ 凸端(ML40Cr/SUS304)

型号	M	L	S	h	d (min)	b (min)
代码	M	L	S	h	d (min)	b (min)
3	(3) 4 5 6 8 10 12		1.5	1.2	1.75	0.75
4	4 5 6 8 10 12 16 20		2	1.5	2.25	1
5	5 6 8 10 12 16 20 25 30		2.5	2	3.2	1.25
6	6 8 10 12 16 20 25 30		3	2	3.7	1.5
8	(6) 8 10 12 16 20 25 30		4	3	5.2	2
10	10 12 16 20 25 30 35 40 45 50		5	4	6.64	2.5
(12)	12 16 20 25 30 35 40 45 50		6	4.8	8.14	3

① 带()尺寸仅适用TAY31。



请按图示订货

■ 平端

型号	M	L	S
代码	M	L	S
TAY01	3	3 4 5 6 8 10	1.5
TAY01—M4—L10	4	3 4 5 6 8 10	2



未税价(元)

● 优惠价

数量	1~49	50~
价格	100% 另行报价	



交货期

3