∢ 防松型 六角螺母

○ 全金属锁紧螺母 总目录

目录 使用说明 螺钉

螺栓

螺柱 铆接类 组合件

垫圈 挡圈 树脂类 带挡块 螺钉 柱塞

紧固件

进口专区 紧固件

专用配件

经济型

轴承

标准型 轴承 进口型 轴承

品牌轴承

带座轴承

吊环

索具

电子焊接 工具 手动工具 电动工具 气动工具 储存工具 量具

刀具 技术资料

代码		类型	螺纹	材	<u></u> 质	表面处理
1 (1)=			1条4人	国标	相当	农山处垤
TBK41	防松螺母	全金属锁紧螺母	粗牙	45	S45C	镀锌
TBK42	別位黎母	土立周坝系琢马	租力	0Cr18Ni9	SUS304	ハレム し



TBK42



‼ 适用标准: DIN 980-1987









型号		螺距P S		h		m	(0)	紧固扭矩N/m	
代码	M	塚 IEP	3		(max)	111	(e)	TBK41	TBK42
	4	0.7	7		4.2	3	8.1	2.2	1.9
(S45C)	5	0.8	8	0 -0.2	5.1	3.9	9.2	4.4	3.8
TBK41	6	1.0	10		6	4.2	11.5	7.4	6.5
	8	1.25	13	0	8	6.1	15	18	16
(SUS304)	10	1.5	17(16)	-0.25	10	7.1	19.6	36	31
TBK42	12	1.75	19(18)	0	12	9	21.9	62	55
	16	2.0	24	-0.35	16	13	27.7	155	135
				•					

● 常()S尺寸适用于TBK41。

请按图示订货





数量	1~4	5~
价格	100%	另行报价



◎ 非金属嵌件六角锁紧螺母

代码		 类型	螺纹	材质	£	表面处理
1 (1)=		突至	1条4人	国标	相当	衣画双连
TBK43	防松螺母	非金属嵌件	粗牙	45	S45C	镀锌
TBK44	別松塚母	六角锁紧螺母	租力	0Cr18Ni9	SUS304	-









! 适用标准: DIN 985-1987





视角标准:第一视角

型号	·	螺距P			0	e (min)
代码	M	\$₩P	m	h	S	
	3	0.5	2.4	4	5.5	6.01
	4	0.7	2.9	5	7	7.66
	5	0.8	3.2	3	8	8.79
	6	1.0	4	6	10	11.05
	8	1.25	5.5	8	13	14.38
	10	1.5	6.5	10	17	18.9
	12	1.75	8	12	19	21.1
(S45C)	14	2.0	9.5	14	22	24.49
TBK43	16	2.0	10.5	16	24	26.75
	18		13	18.5	27	29.56
(SUS304)	20	2.5	14	20	30	32.95
TBK44	(22)		15	22	32	35.03
	24	3.0	15	24	36	39.55
	(27)	3.0	17	27	41	45.2
	(30)	3.5	19	30	46	50.85
	33	3.3	22	33	50	55.37
	36	4.0	25	36	55	60.79
	(39)	4.0	27	39	60	66.44
	(42)	4.5	29	42	65	72.09

! 带()规格不适用TBK44。









