

卡轮式锁模组件 加长型卡轮式锁模组件


	代码	米刑	*型 材质					
۱	1749	英宝		锁紧座	耐温			
l	TFD10	上於一帶出	标准型			- 4		
	TFD11	卡轮式锁模组件	紧凑型	S50C	SK3	80°C		
	TFD12	加上到上於十绺搭和件	标准型	3500	SNS	80 C		
	TFD13	加长型卡轮式锁模组件	紧凑型		- 4			












加长型卡轮式锁模组件







视角标准:第一视角

○ 卡轮式锁模组件

型5	号 规格	L	L ₁	L ₂	Т	Н	H ₁	J	К	Р	P ₁	P ₂	А	A 1	t	t ₁	d	d ₁	拉力(kgf/套) 常温状态下
	1	48	36	25	25 42	22	18	2	2	36	24	22	24	16	9.5	18	6.5		50
	2 5	54	42	25		22	10			40	28				9	16		11	100
标准型	1	65	46		48.5				3.5	50	31	26					7		150
TFD10		73	50	35	40.5	25	20	3.5	3.5	52	33	20	27	19	9.5	17	0	14	300
	5	1 13	30		56.5				11.5	32		34					"	14	400
	6	103	65	48	58	30	24	4	4	76	42	31	34	25	13	19	11	17	500
II 모 V = 파네	1	65	46		48.5				3.5	50	31	26					7	11	150
紧凑型 TFD11		73	50	35	40.5	25	20	3.5	3.5	52	33	20	24	19	9.5	15.5	۵	14	300
11/011	3	1 /3	30		56.5				11.5	52	- 55	34					9	14	400

○ 加长型卡轮式锁模组件

75117																			
型号 代码 规格		L	L ₁	L ₂	Т	Н	H ₁	J	К	Р	P ₁	P ₂	Α	A ₁	t	t ₁	d	d1	拉力(kgf/套) 常温状态下
标准型	1	73	50	35	79.5	25	20	3.5	34.5	52	22	57	27	19	3.5	17	0	1.1	600
TFD12	2	13	50	35	87.5	25	20	3.5	42.5	32	33		21	19	3.5	17	9	14	800
紧凑型	1	73	50	35	87.5	25	20	3.5	42.5	52	33	65	24	19	9.5	15.5	9	14	800
TFD13	2	103	65	48	89	30	24	4	35	76	42		34	25	13	19	11	17	1000











AUTOMATIONEXPER