

型号	内径			a	使用方法						
	代码	D	L		弹簧常数 N/mm	压紧长度 Fmm	负载N	Fmm	负载N	Fmm	负载N
22	50	191	38.7	10.0		9.0		8.0			
	55	174	42.6	11.0		9.9		8.8			
	60	159	46.4	12.0		10.8		9.6			
	65	147	50.3	13.0		11.7		10.4			
	70	137	54.2	14.0		12.6		11.2			
	75	127	58.1	15.0	1912	13.5	1721	12.0	1530		
	80	120	61.9	16.0		14.4		12.8			
	90	106	69.7	18.0		16.2		14.4			
	100	95.6	77.4	20.0		18.0		16.0			
	125	76.5	96.8	25.0		22.5		20.0			
	150	63.7	116.1	30.0		27.0		24.0			
	25	25	481	19.0	5.0		4.5		4.0		
30		400	22.8	6.0		5.4		4.8			
35		343	26.6	7.0		6.3		5.6			
40		300	30.4	8.0		7.2		6.4			
45		267	34.2	9.0		8.1		7.2			
50		240	38.0	10.0		9.0		8.0			
55		218	41.8	11.0		9.9		8.8			
60		200	45.6	12.0		10.8		9.6			
65		185	49.4	13.0		11.7		10.4			
70		172	53.2	14.0	2403	12.6	2162	11.2	1922		
75		160	57.0	15.0		13.5		12.0			
27		25	569	19.0	5.0		4.5		4.0		
	30	474	22.8	6.0		5.4		4.8			
	35	406	26.6	7.0		6.3		5.6			
	40	355	30.4	8.0		7.2		6.4			
	45	316	34.2	9.0		8.1		7.2			
	50	284	38.0	10.0		9.0		8.0			
	55	259	41.8	11.0		9.9		8.8			
	60	237	45.6	12.0		10.8		9.6			
	65	219	49.4	13.0		11.7		10.4			
	70	203	53.2	14.0	2844	12.6	2560	11.2	2275		
	75	190	57.0	15.0		13.5		12.0			
	30	25	706	19.0	5.0		4.5		4.0		
30		588	22.8	6.0		5.4		4.8			
35		504	26.6	7.0		6.3		5.6			
40		441	30.4	8.0		7.2		6.4			
45		392	34.2	9.0		8.1		7.2			
50		353	38.0	10.0		9.0		8.0			
55		321	41.8	11.0		9.9		8.8			
60		294	45.6	12.0		10.8		9.6			
65		272	49.4	13.0		11.7		10.4			
70		252	53.2	14.0	3530	12.6	3177	11.2	2824		
75		235	57.0	15.0		13.5		12.0			
35		25	883	19.0	5.0		4.5		4.0		
	30	711	22.8	6.0		5.4		4.8			
	35	601	26.6	7.0		6.3		5.6			
	40	517	30.4	8.0		7.2		6.4			
	45	453	34.2	9.0		8.1		7.2			
	50	400	38.0	10.0		9.0		8.0			
	55	358	41.8	11.0		9.9		8.8			
	60	326	45.6	12.0		10.8		9.6			
	65	294	49.4	13.0		11.7		10.4			
	70	272	53.2	14.0		12.6		11.2			
	75	252	57.0	15.0		13.5		12.0			

型号	内径			a	使用方法						
	代码	D	L		弹簧常数 N/mm	压紧长度 Fmm	负载N	Fmm	负载N	Fmm	负载N
40	40	600	31.0	8.0		7.2		6.4			
	45	534	34.8	9.0		8.1		7.2			
	50	480	38.7	10.0		9.0		8.0			
	55	437	42.6	11.0		9.9		8.8			
	60	400	46.4	12.0		10.8		9.6			
	65	369	50.3	13.0		11.7		10.4			
	70	343	54.2	14.0		12.6		11.2			
	75	320	58.1	15.0	4802	13.5	4322	12.0	3842		
	80	300	61.9	16.0		14.4		12.8			
	90	267	69.7	18.0		16.2		14.4			
	100	240	77.4	20.0		18.0		16.0			
	45	25	481	19.0	5.0		4.5		4.0		
30		400	22.8	6.0		5.4		4.8			
35		343	26.6	7.0		6.3		5.6			
40		300	30.4	8.0		7.2		6.4			
45		267	34.2	9.0		8.1		7.2			
50		240	38.0	10.0		9.0		8.0			
55		218	41.8	11.0		9.9		8.8			
60		200	45.6	12.0		10.8		9.6			
65		185	49.4	13.0		11.7		10.4			
70		172	53.2	14.0		12.6		11.2			
75		160	57.0	15.0		13.5		12.0			
50		25	569	19.0	5.0		4.5		4.0		
	30	474	22.8	6.0		5.4		4.8			
	35	406	26.6	7.0		6.3		5.6			
	40	355	30.4	8.0		7.2		6.4			
	45	316	34.2	9.0		8.1		7.2			
	50	284	38.0	10.0		9.0		8.0			
	55	259	41.8	11.0		9.9		8.8			
	60	237	45.6	12.0		10.8		9.6			
	65	219	49.4	13.0		11.7		10.4			
	70	203	53.2	14.0		12.6		11.2			
	75	190	57.0	15.0		13.5		12.0			
	60	25	706	19.0	5.0		4.5		4.0		
30		588	22.8	6.0		5.4		4.8			
35		504	26.6	7.0		6.3		5.6			
40		441	30.4	8.0		7.2		6.4			
45		392	34.2	9.0		8.1		7.2			
50		353	38.0	10.0		9.0		8.0			
55		321	41.8	11.0		9.9		8.8			
60		294	45.6	12.0		10.8		9.6			
65		272	49.4	13.0		11.7		10.4			
70		252	53.2	14.0		12.6		11.2			
75		235	57.0	15.0		13.5		12.0			

请按图示订货

代码	型号	内径
YSWB	J-YSWB	3
D	L	
6	20	

YSWB-D6-L15

● 优惠价

数量	1~9	10~
价格	100%	另行报价

未税价(元)

交货期

3