


压缩弹簧

外径基准不锈钢型

代码	类型		材质		允许位移量	弹簧常数公差
			国标	相当		
YUBB	外径基准 不锈钢型	标准型	0Cr18Ni9	SUS304-WPB	L×(15~25)%	±10%
E-YUBB		经济型				
J-YUBB		进口型				



D尺寸公差		L尺寸公差	
D	公差	L	公差
10以下	0 -0.5	50以下	±1.5
12以上	-0.8	55以上	±2.5



- ① 压紧长度为参考值，制作时会有少许差异。
- ② 使用次数：100万次。
- ③ 带()的L规格两端均未进行磨削加工。
- ④ 此系列产品因结构升级改进，产品尺寸略有变动，新旧款交替期间，出货时可能有不同款产品，均不影响使用。



代码	型号		d	压紧长度	F max	允许负载 Nmax	弹簧常数 N/mm
	D	L					
4	5	(5)	0.55	3.3	1.25	6.1	4.88
		10*	0.65	7	2.5	12.3	4.92
		15*	0.7	10.3	3.75	18.4	4.91
	20	20*	0.75	14.4	5	24.5	4.90
		25	0.8	19.4	5	24.5	4.90
		5*	0.6	2.9	1.25	6.1	4.88
	5	10*	0.75	6.9	2.5	12.3	4.92
		15*	0.8	9.8	3.75	18.4	4.91
		20*	0.85	13.4	5	24.5	4.90
	5	25	0.9	17.8	6.25	30.6	4.90
		30	0.9	21.8	7.5	36.8	4.91
		5	0.8	3.6	1.25	12.3	9.84
10*	10*	0.9	6.8	2.5	24.5	9.80	
	15*	1	10.5	3.75	36.8	9.81	
	20*	1.1	14.6	5	49	9.80	
25*	25*	1.1	17.9	6.25	61.3	9.81	
	30	1.2	23.1	6	58.8	9.80	
	35	1.2	27.3	7	68.6	9.80	
40	40	1.2	31.2	8	78.5	9.81	
	45	1.3	34.8	9	88.3	9.81	
	50	1.3	38.4	10	98.1	9.81	
60	60	1.3	44.2	9	88.3	9.81	
	70	1.4	58.5	10.5	103	9.81	
	10*	1.1	6.9	2.5	24.5	9.80	
15*	15*	1.2	9.9	3.75	36.8	9.81	
	20*	1.3	14	5	49	9.80	
	25*	1.3	14.5	6.25	61.3	9.81	
30	30	1.4	21.4	7.5	73.5	9.80	
	35	1.4	23.8	8.75	85.8	9.81	
	40	1.5	28.9	10	98.1	9.81	
45	45	1.5	32.6	11.25	110	9.78	
	10	1.3	7.2	2.5	24.5	9.80	
	15*	1.4	10.2	3.75	36.8	9.81	
20*	20*	1.5	13.9	5	49	9.80	
	25*	1.5	16.1	6.25	61.3	9.81	
	30*	1.6	20.4	7.5	73.5	9.80	
35	35	1.6	22.8	8.75	85.8	9.81	
	40	1.7	27.2	10	98.1	9.81	
	45	1.7	29.75	11.25	110	9.78	
50	50	1.8	36.5	12.5	123	9.84	
	60	1.8	41.4	15	147	9.80	
	70	1.9	50.8	17.5	172	9.83	
15*	15*	1.5	9.4	3.75	36.8	9.81	
	20*	1.6	12.4	5	49	9.80	
	25	1.7	16.2	6.25	61.3	9.81	
30*	30*	1.8	20.3	7.5	73.5	9.80	
	40	1.9	28	10	98.1	9.81	
	50	2	35.5	12.5	123	9.84	
60	60	2.1	43.6	15	147	9.80	
	70	2.1	48.8	17.5	172	9.83	
	80	2.2	58.5	20	196	9.80	
15*	15*	1.8	9.5	3.75	73.5	19.60	
	20*	1.9	12.9	5	98.1	19.62	
	25*	2	17	6.25	123	19.68	
30*	30*	2.1	20.5	7.5	147	19.60	
	40*	2.3	28.2	10	196	19.60	
	45	2.3	32.2	11.25	221	19.64	
50	50	2.4	36	12.5	245	19.60	
	60	2.5	44.4	12	235	19.58	
	70	2.6	54	14	275	19.64	

代码	型号		d	压紧长度	F max	允许负载 Nmax	弹簧常数 N/mm
	D	L					
14	15	15	1.9	10	3.75	73.5	19.60
		20	2	13.5	5	98.1	19.62
		25	2.1	16.3	6.25	123	19.68
	20	30	2.3	21.3	7.5	147	19.60
		35	2.4	24.7	8.75	172	19.66
		40	2.4	28.2	10	196	19.60
	25	60	2.6	43.6	15	294	19.60
		80	2.7	61.4	16	314	19.63
		15	2	10	3.75	73.5	19.60
	20*	20*	2.1	12.1	5	98.1	19.62
		25	2.3	17.3	6.25	123	19.68
		30*	2.4	21	7.5	147	19.60
35	35	2.5	24.4	8.75	172	19.66	
	40	2.6	28	10	196	19.60	
	45	2.7	31.7	11.25	221	19.64	
50	50	2.7	36.66	12.5	245	19.60	
	60	2.9	43.5	15	294	19.60	
	70	2.9	49.4	17.5	343	19.60	
80	80	3	59.3	16	314	19.63	
	25*	2.9	16.7	6.25	184	29.44	
	30*	3	20.3	7.5	221	29.47	
35	35	3	22.7	8.75	257	29.37	
	40	3.2	27.2	10	294	29.40	
	45	3.2	29.6	9	265	29.44	
50	50	3.4	38.3	10	294	29.40	
	60	3.5	44.6	12	353	29.42	

- ① 允许位移量Fmax：表示弹簧允许压缩的最大长度，超出此压缩量使用弹簧会缩短。
- ② 允许负载Nmax：表示压缩Fmax的负载，单位N。
- ③ 弹簧常数N/mm=(Nmax)/(Fmax)。
- ④ 经济型仅适用带*号规格。

请按图示订货

型号			
代码	D	L	d
YUBB			0.55
E-YUBB	4		0.65

YUBB - D4 - L5

优惠价

数量	1~9	10~
价格	100%	另行报价

未税价(元)

交货期

① 经济型仅适用带*号规格。