


塔簧

| 代码 | 类型 | 材质 | | 表面处理 | 旋转方向 |
|-----|----|----------|------------|------|------|
| | | 国标 | 相当 | | |
| YUE | 塔簧 | 0Cr18Ni9 | SUS304-WPB | — | 右向 |
| YWE | | 弹簧钢 | SWP-A | 发黑 | |

- ① 弹簧常数公差±10%;
- ② 两端均未进行磨削加工。



视角标准：第一视角

| 型号 | | 自由长度 L | 线径 d | 外径 D ₁ | 有效圈数 | | F _{max} | 允许负载 N _{max} | | 初始弹簧常数 N/mm | |
|------------|-----|-----------|---------|----------------------|--------|--------|------------------|--------------------------|-------|----------------|-------|
| 代码 | 外径D | | | | n | 公差 | | SUS304-WPB | SWP-A | SUS304-WPB | SWP-A |
| YUE YWE | 9 | 8 | 0.5 | 4 | 5 | ±0.25 | 5 | 2.130 | 2.428 | 0.421 | 0.480 |
| | 10 | 11 | | | 7 | 2.290 | 2.611 | 0.323 | 0.368 | | |
| | | 15 | | | 6.5 | ±0.5 | 10 | 2.700 | 3.078 | 0.245 | 0.279 |
| | 11 | 20 | | | 7.5 | ±0.25 | 13 | 3.050 | 3.477 | 0.216 | 0.246 |
| | | 10 | 5 | ±0.25 | 7 | 3.440 | 3.922 | 0.470 | 0.536 | | |
| | 12 | 13 | 5.5 | ±0.5 | 9 | 3.230 | 3.682 | 0.343 | 0.391 | | |
| | | 17 | 6.5 | ±0.5 | 12 | 4.080 | 4.651 | 0.294 | 0.335 | | |
| | | 22 | 7.5 | ±0.25 | 15 | 4.370 | 4.982 | 0.255 | 0.291 | | |
| | 13 | 12 | 5 | ±0.25 | 8 | 8.810 | 10.043 | 0.921 | 1.050 | | |
| | | 16 | 5.5 | ±0.5 | 12 | 7.830 | 8.926 | 0.578 | 0.659 | | |
| | 15 | 20 | 6.5 | ±0.5 | 14 | 8.530 | 9.724 | 0.490 | 0.559 | | |
| | | 25 | 7.5 | ±0.25 | 17.5 | 9.700 | 11.058 | 0.382 | 0.435 | | |
| | 18 | 15 | 5 | ±0.25 | 10.5 | 9.330 | 10.636 | 0.843 | 0.961 | | |
| | | 19 | 5.5 | ±0.5 | 15 | 10.500 | 11.970 | 0.588 | 0.670 | | |
| | 20 | 24 | 7 | ±0.5 | 16.8 | 9.960 | 11.354 | 0.461 | 0.526 | | |
| | | 30 | 8.5 | ±0.25 | 21 | 11.900 | 13.566 | 0.382 | 0.435 | | |
| | 22 | 20 | 5 | ±0.25 | 15 | 15.400 | 17.556 | 0.941 | 1.073 | | |
| | | 25 | 5.5 | ±0.5 | 19 | 13.400 | 15.276 | 0.617 | 0.703 | | |
| | 25 | 32 | 7 | ±0.5 | 23.5 | 15.000 | 17.100 | 0.480 | 0.547 | | |
| | | 40 | 8.5 | ±0.25 | 28 | 15.000 | 17.100 | 0.402 | 0.458 | | |
| 27 | 25 | 5 | ±0.25 | 17.5 | 23.600 | 26.904 | 1.670 | 1.904 | | | |
| | 30 | 5.5 | ±0.5 | 22.5 | 29.700 | 33.858 | 1.160 | 1.322 | | | |
| 30 | 37 | 7.5 | ±0.5 | 24.5 | 28.200 | 32.148 | 0.843 | 0.961 | | | |
| | 45 | 9 | ±0.25 | 29 | 28.500 | 32.490 | 0.706 | 0.805 | | | |



| 型号 | | | |
|-----|-----|-------|-----|
| 代码 | 外径D | 自由长度L | 线径d |
| YUE | 9 | 8 | 0.5 |
| YWE | 10 | 11 | |

YUE—D9—L8



| ● 优惠价 | 数量 | |
|-------|------|------|
| | 1~9 | 10~ |
| 价格 | 100% | 另行报价 |

| 交货期 |
|-----|
| 5 |

