


微型陶瓷轴承

◀ 无防尘盖式


代码	类型	材质			推荐使用最高温度
		套圈	球体	保持架	
BBD01	标准型	ZrO2	ZrO2	PTFE	240℃
BBD02	满球型			—	500℃





标准型
BBD01




■ 安装图



满球型
BBD02



■ 安装图



视角标准：第一视角

型号		d	D	B	r1	安装尺寸			参考重量 (g)
代码	轴承型号					db(min)	da(max)	r(max)	
	683	3	7	3	0.1	3.9	5.8	0.1	0.24
	693		8	4			6.8		0.50
	603		9	3		4.2	7.8	0.15	0.70
	623		10		0.15		8.8		1.30
	684	4	9			5	7.8	0.1	0.50
	694		11	4		5.2	9.8	0.15	1.30
	604		12				10.4		1.70
	624		13		0.2	5.6	11.4		2.30
	685	5	11	5	0.15	6.2	9.8	0.2	0.90
	695		13	4	0.2	6.6	11.4		1.90
	605		14				12.4		2.70
	625		16		0.3	7	14	0.3	3.80
	686	6	13	5	0.16	7	11.8		1.50
	696		15		0.2	7.6	13.4	0.2	3
	606		17				15		4.60
	626		19	6	0.3	8	17	0.3	6.30
	687	7	14	5	0.15	8.2	12.8	0.15	1.70
	697		17				15		4
	607		19	6	0.3	9	17	0.3	5.90
	627		22	7			20		9.80
	688	8	16	5	0.2	9.6	14.4	0.2	2.50
	698		19	6			17		5.60
	608		22	7	0.3	10	20	0.3	9.30
	628		24	8			22		13
	689	9	17	5	0.2	10.6	15.4	0.2	2.70
	699		20	6	0.3		18		6.50
	609		24	7		11		0.3	11
	629		26	8	0.6	13	22		15

轴承
关节轴承

E7

标准型
BBD01
满球型
BBD02



请按图示订货

型号		d	D	B
代码	轴承型号			
BBD01	683	3	7	3
BBD02	693		8	4

BBD01—683



未税价(元)

● 优惠价

数量 1~9 10~
价格 100% 另行报价



交货期

7