






代码	类型	材质			推荐使用最高温度
		套圈	球体	保持架	
BBD11	标准型	ZrO2	ZrO2	PTFE	200℃
BBD12				PEEK	220℃
BBD21	满球型			—	350℃

标准型
BBD11/12

安装图

满球型
BBD21

安装图



视角标准：第一视角



型号		d	D	B	r1	安装尺寸				参考重量 (g)
代码	轴承型号					db		da	r	
						(min)	(max)	(max)	(max)	
标准型 BBD11 BBD12	6800	10	19	5	0.3	12	12.5	17	0.3	4
	6900		22	6			13	20		7
	6000		26	8			13.5	24		14
	6200		30	9			16	26		25
	6300	12	35	11	0.6	14	16.5	31	0.6	40
	6801		21	5			14.5	19		5
	6901		24	6			15	22		8
	6001		28	8			16	26		17
	6201		32	10			17	28		28
	6301		37	12			18	32		46
	6802	15	24	5	0.3	17	22	26	0.3	5
	6902		28	7			17.5	26		12
	6002		32	9			19	30		24
	6202		35	11			20	31		35
	6302		42	13			20	37		64
	6803	17	26	5	1.0	19	19.5	24	0.6	5
	6903		30	7			20	28		13
	6003		35	10			21	33		32
	6203		40	12			23	36		52
	6303		47	14			25.5	42		87
	6804	20	32	7	0.3	22	22.5	30	0.3	13
	6904		37	9			24	35		28
	6004		42	12			26	38		52
	6204		47	14			25	42		82
	6304	25	52	15	1.1	26.5	28	45.5	1.0	110
	6805		37	7			35	40		16
	6905		42	9			29	40		32
	6005		47	12			30.5	43		61
满球型 BBD21	6205	30	52	15	1.0	30	32	47	1.0	99
	6305		62	17			31.5	55.5		180
	6806		42	7			33	40		18
	6906		47	9			32	34		40
	6006	35	55	13	1.0	35	37	50	0.3	89
	6206		62	16			39	57		150
	6306		72	19			36.5	42.5		270
	6807		47	7			37	38		21
	6907	40	55	10	0.6	39	40	51	0.6	58
	6007		62	14			40	42		120
	6207		72	17			41.5	45		220
	6307		80	21			43	47		360
	6808	45	52	7	0.3	42	43	50	0.3	20
	6908		62	12			44	45		90
	6008		68	15			45	47		150
	6208		80	18			46.5	51		280
	6308	50	90	23	1.5	48	53	82	1.5	490
	6809		58	7			47	47.5		29
	6909		68	12			49	50		97
	6009		75	16			50	53.5		190
	6209	55	85	19	1.1	51.5	55.5	78.5	1.0	320
	6309		100	25			53	61.5		640
	6810		65	7			52	52.5		38
	6910		72	12			54	55		100
	6010	60	80	16	1.0	55	57.5	75	1.0	200
	6210		90	20			56.5	60		350
	6310		110	27			59	68		820



请按图示订货

型号		d	D	B
代码	轴承型号			
BBD11	6800	10	19	5
BBD12	6900		22	6

BBD11—6800



未税价(元)

● 优惠价

数量	1~9	10~
价格	100%	另行报价

交货期
7