

# 组合型·DB/DF配对·无密封圈

## 标准型 接触角15° P5精度


# 成对双联角接触球轴承




| 代码    | 类型  |     | 轴承类型<br>代码 | 轴承精度          | 轴承材质  |      | 接触角<br>(°) |
|-------|-----|-----|------------|---------------|-------|------|------------|
|       |     |     |            |               | 国标    | 相当   |            |
| BBQ06 | 组合型 | 标准型 | 7          | GB/T 307.1 5级 | GCr15 | SUJ2 | 15         |

① 出厂前未封入润滑脂，请在使用前封入。


-DB(反面)





安装图



-DF(正面)



安装图



视角标准：第一视角

| 型号    |       |            | d  | D   | B   | r<br>(min) | r1<br>(min) | 基本额定负载<br>(KN) |        | 容许转速<br>rpm(参考) |        | 作用点a  |      | 安装尺寸    |         |         |         |         |         | 重量<br>kg<br>(参考) |
|-------|-------|------------|----|-----|-----|------------|-------------|----------------|--------|-----------------|--------|-------|------|---------|---------|---------|---------|---------|---------|------------------|
| 代码    | 轴承型号  | 组合<br>形式   |    |     |     |            |             | Cr(动)          | Cor(静) | 脂润滑             | 油润滑    | DB    | DF   | DB      |         |         | DF      |         |         |                  |
|       |       |            |    |     |     |            |             |                |        |                 |        |       |      | da(min) | da(max) | ra(max) | da(min) | da(max) | ra(max) |                  |
| BBQ06 | 706   |            | 6  | 17  | 6   |            |             | 2.54           | 1      | 110000          | 170000 | 10    |      | 8       | 15.6    |         | 8       | 15      |         | 0.01             |
|       | 708   |            | 8  | 22  | 7   | 0.3        | 0.15        | 3.81           | 1.6    | 87000           | 130000 | 12    | 2    | 10      | 20.6    | 0.3     | 10      | 20      | 0.15    | 0.02             |
|       | 7201* |            | 12 | 32  | 10  |            |             | 12.83          | 7.68   | 29400           | 39200  | 15.9  | —    | 17      | 29.5    |         | —       | —       | —       | 0.034            |
|       | 7005  |            | 25 | 47  | 12  | 0.6        | 0.3         | 18.95          | 14.88  | 17400           | 23200  | 21.6  | 2.4  | 30      | 44.5    | 0.6     | 30      | 42      | 0.3     | 0.091            |
|       | 7206  |            | 30 | 62  | 16  |            |             | 37.26          | 29.4   | 13800           | 18400  | 28.3  | 3.7  | 36      | 58.5    |         | 36      | 56      |         | 0.19             |
|       | 7007  |            | 35 | 62  | 14  | 1          |             | 30.94          | 27.4   | 13000           | 18000  | 27    | 1    | 41      | 58.5    |         | 41      | 56      |         | 0.16             |
|       | 7008  | DB<br>(反面) | 40 | 68  | 15  |            |             | 33.37          | 31.8   | 11000           | 15000  | 29.5  | 0.5  | 46      | 64.5    |         | 46      | 62      |         | 0.219            |
|       | 7209  |            | 45 | 85  | 19  | 1.1        | 0.6         | 61.72          | 55.6   | 10000           | 14000  | 36.4  | 1.6  | 52      | 80      | 1       | 52      | 78      | 0.6     | 0.395            |
|       | 7010  |            | 50 | 80  | 16  | 1          |             | 41.47          | 41.4   | 9600            | 12800  | 33.4  | 1.4  | 56      | 76.5    |         | 56      | 74      |         | 0.3              |
|       | 7210  | DF<br>(正面) |    |     | 20  |            |             | 72.58          | 68     | 9000            | 12000  | 38.7  | 1.3  | 57      | 85      |         | 57      | 83      |         | 0.448            |
|       | 7011  |            |    | 90  | 18  |            |             | 59             | 58.2   |                 | 8400   | 37.4  | 1.4  | 62      | 85      |         | 62      | 83      |         | 0.21             |
|       | 7211  |            |    | 55  | 21  | 1.5        | 1           | 85.7           | 79.8   |                 |        | 41.7  | 0.3  | 63.5    | 94.5    | 1.5     | 63.5    | 91.5    | 1       | 0.589            |
|       | 7013  |            |    | 65  | 100 | 18         | 1.1         | 0.6            | 67.2   | 74.4            | 7800   | 10400 | 40.1 | 4.1     | 72      | 95      | 1       | 72      | 93      | 0.6              |
|       | 7216  |            | 80 | 140 | 26  | 2          | 1           | 151            | 163    |                 | 5900   | 55.5  | 3.5  | 90      | 134     | 2       | 90      | 130     | 1       | 1.36             |
|       | 7017  |            | 85 | 130 | 22  | 1.1        | 0.6         | 97.5           | 117.2  |                 |        | 50.8  |      | 92      | 125     | 1       | 92      | 123     | 0.6     | 1.02             |
|       | 7018  |            | 90 | 140 | 24  | 1.5        | 1           | 107.9          | 131.6  | 5500            | 7300   | 54.8  | 6.8  | 98.5    | 134.5   | 1.5     | 98.5    | 131.5   |         | 1.31             |
|       | 7019  |            |    | 145 |     |            |             | 119.1          | 146.4  | 5300            | 7000   | 56.1  | 8.1  | 103.5   | 139.5   |         | 103.5   | 136.5   | 1       | 1.37             |
|       | 7219  |            | 95 | 170 | 32  | 2          | 1.1         | 214.8          | 223.8  | 4900            | 6600   | 67.5  | 3.5  | 107     | 163     | 2       | 107     | 158     |         | 2.62             |

① \* 7201无DF(正面)组合形式。

① 1kgf=9.81N



| 型号    |      | 组合<br>形式 |
|-------|------|----------|
| 代码    | 轴承型号 |          |
| BBQ06 | 706  | DB       |
|       | 708  | DF       |

BBQ06—706DB



未税价(元)

● 优惠价

| 数量 | 1~9  | 10~  |
|----|------|------|
| 价格 | 100% | 另行报价 |

| 交货期 |
|-----|
| 6   |