精密锁紧螺母

◀ 缩紧锁紧型

总目录 使用说明

螺钉

螺栓

螺柱

铆接类

组合件

螺母

垫圈

挡圈

树脂类 带挡块 螺钉

柱塞 紧固件

进口专区 紧固件 专用配件 经济型

轴承

进口型 轴承

品牌轴承

带座轴承

吊环

索具

电子焊接 工具

手动工具

电动工具 气动工具

储存工具


量具


刀具

技术资料



◎ 特点:该产品通过螺母本身的弹性变形,使螺纹面紧 密贴合于外螺纹, 实现轴向强力紧固。其锁紧能力优 异,适用于易松脱、高扭矩、工作条件恶劣的场合。







螺纹精度: ISO 4H 端面偏摆: 0.005





视角标准:	第一视角

五	<u></u> 号	ARR OF	_						扭紧力矩
代码 公称尺寸		螺距	D	Н	d	С	n-b	n-M×L	(NM)
		0.75		14			3-2.5		
	M10		24	15	22	17		3-M3×10	2
	M12	1.0	26	14	25	5 19 3-3	3-3		_
	M15		33		31	23.5		3-M4×10	3
	M17		37		32	26			
	M18	1.5	38		34	28			
		1.0		18			4-4		
	M20	1.5	40		36	30		4-M4×12	
	M22		42		38	32			
	M24		44			34			
	M25				41	35			
	M26		45						
	M27					37		14	B PB
	M28		46	20	43			4-M4×14	(a
	M30		48		45	39			
	M32		50			0.			CR1
	M33				47	41	4-5	1	3.5
	M35	1.5	53		50	44		TIONE	
	M36								
	M38						- M	4-M4×16	
BKC01	M39		56	22	53	47	UTOM		
BRCUI	M40		58		55	49			
	M42		60		57	51			
	M45		68		63	57		6-M4×16	
	M48		69		65	58			
			70		00	00			
	M50	2.0	70	25	66	60		6-M4×18	
	M52		72		68	62			
	M55	1.5	75		74	0.5			
	M55	2.0	/5		71	65			
	M56	1.5				70	6-6		
		2.0	82	26	77				
	M58							6-M5×18	
		1.5	0.4		79	72			4.5
	M60	2.0	84		79	12			4.5
	M62	1.5							
	M64	1.5	86	28	82	75		C MEYOO	
		2.0						6-M5×20	
	M65	1.5	88		84	77			

100/15 (3/4) All (10/15							71- 150715		
	号	螺距	D	н	d	С	c n-b	n-M×L	扭紧力矩
代码	公称尺寸	ASSUE	D	- 11	u		11-0	II-WAL	(NM)
	M65	2.0	88		84	77	6-6		
	M68	1.5	93			80			
	IVIOO	2.0	93	Q	89	00			
	M70	1.5	95		09	82		6-M5×20	
	W 7 U	2.0	95	28		02	6-7		4.5
	M72	1.5	97	91	0.1	84			
	WI72	2.0	97		91	04			
	M75	1.5	100		94	87			
	WI75		100		94	07			
	M80		110		103	95			
	M85		115		108	100			
刮	M90		120		113	105			
	M95			32	118	110		C MC00	
	M100	2.0			123	115		6-M6×22	
	M105		135		128	120	6-8		
	M110		140		133	125			
	M115		145	34	138	130			8
	M120		155		146	136			
	M125	3.0	160	36	150	140		6-M6×25	
	M130		165		156	148			
	M140	2.0		38					
BKC01		3.0	180		168	160			
	M150	2.0						8-M6×25	
		1			178	170			
	M160		205		193	182			
	M170		215		204	193			
	M180	3.0	230		216	205		8-M8×30	
	M190		240		226	215	8-10	2 30	
	M200		245	40	234	223	0 .0		
	M210	4.0			253			8-M8×25	18
		3.0	265		255	243			
	M220	4.0			253			8-M8×30	
	M230		275		265	251			
	M235	3.0			270	257			
	M240		285		275	261			
	M250	4.0	295	42	285	271		8-M10×30	
	M260	3.0	305	72	295	283		5 WI 107-00	
	M280	P	325		315	303	8-12		35
	M300	4.0	345		335	323			
	191500	-	343		333	323			



	10	Ø
按图示证	T俗	ВK

五	빌号	488 OC	D			
代码	公称尺寸	马跃吐巴	D			
ØV.COM	4410	0.75	24			
BRCU	WI IV	1	24			
BKC01-M10-0.75						
代码 ®KCOD BKCO1-	公称尺寸	1	24			





