


KGBAL(科锦)杆端关节轴承

外圈滑动表面带保护层

正常系列(SI...T/K系列)/(SA...T/K系列)

内螺纹

系列	类型	润滑装置	壳体		外圈		内圈	
			材质	表面处理	材质	材质	热处理	
SI...T/K-KGBAL	内螺纹	自润滑	碳钢	镀环保白锌	铜	轴承钢	淬火	



型号		d	d ₃ (6H)	B	C ₁	L ₃ min	W	d ₂	h ₁	L ₄	L ₅	d ₄	d ₅	d _k	a°≈	额定负载(KN)		重量 (kg)
右螺纹	左螺纹															动(Cr)	静(Cor)	
SI5T/K-KGBAL	SIL5T/K-KGBAL	5	M5×0.8	8	6	10	9	18	27	36	4	8.5	11	11.11	13	5.7	6	0.016
SI6T/K-KGBAL	SIL6T/K-KGBAL	6	M6×1.0	9	6.75	12	11	20	30	40	5	10	13	12.7	13	7.2	7.65	0.022
SI8T/K-KGBAL	SIL8T/K-KGBAL	8	M8×1.25	12	9	16	14	24	36	48	5	12.5	16	15.875	14	11.6	12.9	0.047
SI10T/K-KGBAL	SIL10T/K-KGBAL	10	M10×1.5	14	10.5	20	17	28	43	57	6.5	15	19	19.05	13	14.5	18	0.077
SI10-1T/K-KGBAL	SIL10-1T/K-KGBAL	10	M10×1.25	14	10.5	20	17	28	43	57	6.5	15	19	19.05	13	14.5	18	0.077
SI12T/K-KGBAL	SIL12T/K-KGBAL	12	M12×1.75	16	12	22	19	32	50	66	6.5	17.5	22	22.225	13	17	24	0.1
SI12-1T/K-KGBAL	SIL12-1T/K-KGBAL	12	M12×1.25	16	12	22	19	32	50	66	6.5	17.5	22	22.225	13	17	24	0.1
SI14T/K-KGBAL	SIL14T/K-KGBAL	14	M14×2.0	19	13.5	25	22	36	57	75	8	20	25	25.4	16	24	31	0.16
SI14-1T/K-KGBAL	SIL14-1T/K-KGBAL	14	M14×1.5	19	13.5	25	22	36	57	75	8	20	25	25.4	16	24	31	0.16
SI16T/K-KGBAL	SIL16T/K-KGBAL	16	M16×2.0	21	15	28	22	42	64	85	8	22	27	28.575	15	28.5	39	0.22
SI16-1T/K-KGBAL	SIL16-1T/K-KGBAL	16	M16×1.5	21	15	28	22	42	64	85	8	22	27	28.575	15	28.5	39	0.22
SI18T/K-KGBAL	SIL18T/K-KGBAL	18	M18×1.5	23	16.5	32	27	44	71	93	10	25	31	31.75	15	42.5	47.5	0.32
SI20T/K-KGBAL	SIL20T/K-KGBAL	20	M20×1.5	25	18	33	30	50	77	102	10	27.5	34	34.925	14	42.5	57	0.42
SI22T/K-KGBAL	SIL22T/K-KGBAL	22	M22×1.5	28	20	37	32	54	84	111	12	30	38	38.1	15	57	68	0.54
SI25T/K-KGBAL	SIL25T/K-KGBAL	25	M24×2.0	31	22	42	36	60	94	124	12	33.5	42	42.86	15	68	85	0.72
SI28T/K-KGBAL	SIL28T/K-KGBAL	28	M27×2.0	35	24	51	41	66	103	136	14	37	46	47.63	15	86	107	0.82
SI30T/K-KGBAL	SIL30T/K-KGBAL	30	M30×2.0	37	25	51	41	70	110	145	15	40	50	50.8	17	88	114	1.1



请按图示订货



型号
SI5T/K-KGBAL

未税价(元)

● 优惠价
数量 1~9 10~
价格 100% 另行报价交货期
5

外螺纹

系列	类型	润滑装置	壳体		外圈		内圈	
			材质	表面处理	材质	材质	热处理	
SA...T/K-KGBAL	外螺纹	自润滑	碳钢	镀环保白锌	铜	轴承钢	淬火	



型号		d	d ₃ (6g)	B	C ₁	L ₁ min	d ₂	h	L ₂	d _k	R ₁	a°≈	额定负载(KN)		重量 (kg)
右螺纹	左螺纹												动(Cr)	静(Cor)	
SA5T/K-KGBAL	SAL5T/K-KGBAL	5	M5×0.8	8	6	19	18	33	42	11.1	0.3	13	5.7	6	0.01
SA6T/K-KGBAL	SAL6T/K-KGBAL	6	M6×1.0	9	6.75	21	20	36	46	12.7	0.3	13	7.2	12.9	0.02
SA8T/K-KGBAL	SAL8T/K-KGBAL	8	M8×1.25	12	9	25	24	42	54	15.875	0.3	14	11.6	7.65	0.04
SA10T/K-KGBAL	SAL10T/K-KGBAL	10	M10×1.5	14	10.5	28	28	48	62	19.105	0.3	13	14.5	18	0.06
SA12T/K-KGBAL	SAL12T/K-KGBAL	12	M12×1.75	16	12	32	32	54	70	22.225	0.3	13	17	24	0.09
SA12-1T/K-KGBAL	SAL12-1T/K-KGBAL	12	M12×1.25	16	12	32	32	54	70	22.2	0.3	13	17	24	0.09
SA14T/K-KGBAL	SAL14T/K-KGBAL	14	M14×2.0	19	13.5	36	36	60	78	25.4	0.3	16	24	31	0.14
SA16T/K-KGBAL	SAL16T/K-KGBAL	16	M16×2.0	21	15	37	42	66	87	28.575	0.3	15	28.5	39	0.21
SA16-1T/K-KGBAL	SAL16-1T/K-KGBAL	16	M16×1.5	21	15	37	42	66	87	28.575	0.3	15	28.5	39	0.28
SA18T/K-KGBAL	SAL18T/K-KGBAL	18	M18×1.5	23	16.5	41	44	72	94	31.75	0.3	15	42.5	47.5	0.28
SA20T/K-KGBAL	SAL20T/K-KGBAL	20	M20×1.5	25	18	45	50	78	103	34.925	0.3	14	42.5	57	0.38
SA22T/K-KGBAL	SAL22T/K-KGBAL	22	M22×1.5	28	20	48	54	84	111	38.1	0.3	15	57	68	0.48
SA25T/K-KGBAL	SAL25T/K-KGBAL	25	M24×2.0	31	22	55	60	94	124	42.86	0.3	15	68	85	0.64
SA28T/K-KGBAL	SAL28T/K-KGBAL	28	M27×2.0	35	24	62	66	103	136	47.63	0.3	15	86	107	0.8
SA30T/K-KGBAL	SAL30T/K-KGBAL	30	M30×2.0	37	25	66	70	107	145	50.8	0.3	17	88	114	1.1



请按图示订货

型号
SA5T/K-KGBAL

未税价(元)

● 优惠价
数量 1~9 10~
价格 100% 另行报价交货期
5