

双列圆柱滚子轴承

◀ 外圈无挡边
带油孔/油槽








品牌	类型	油槽/油孔	轴承精度	后置代码	轴承材质	
					国标	相当
HRB	外圈无挡边	有	P5	未标记：圆柱孔 K：圆锥孔，锥度1:12 W33：轴承外圈有润滑油槽和3个润滑油孔	GCr15	SUJ2
			P4			

圆柱孔型

圆锥孔型

■ 安装图

■ 安装图



视角标准：第一视角

圆柱孔型	型号		d	D	B	r ₁ (mm)	E _w	额定载荷(KN)		极限转速(r/min)		安装尺寸			重量(kg) 参考	
	P5精度	P4精度						Cr(动)	Cor(静)	脂润滑	油润滑	d _a (mm)	D _a (max)(mm)	f _a (max)		
—	NN3005K/P5W33-HRB	NN3005K/P4W33-HRB	25	47	16	0.6	41.3	26	31.3	19000	22000	29	43	42	0.6	0.12
NN3006/P5W33-HRB	NN3006K/P5W33-HRB	NN3006K/P4W33-HRB	30	55	19		48.5	35.2	41.6	16000	18000	35	50	49		0.19
NN3007/P5W33-HRB	NN3007K/P5W33-HRB	NN3007K/P4W33-HRB	35	62	20		55	37.7	47.5	14000	16000	40	57	56		0.25
NN3008/P5W33-HRB	NN3008K/P5W33-HRB	NN3008K/P4W33-HRB	40	68	21	1	61	44.6	57.4	12000	14000	45	63	62		0.28
NN3009/P5W33-HRB	NN3009K/P5W33-HRB	NN3009K/P4W33-HRB	45	75			67.5	52.8	77.9	11000	13000	50	70	69		0.37
NN3010/P5W33-HRB	NN3010K/P5W33-HRB	NN3010K/P4W33-HRB	50	80	23		72.5	56.5	78.5	10000	12000	55	75	74		0.41
NN3011/P5W33-HRB	NN3011K/P5W33-HRB	NN3011K/P4W33-HRB	55	90			81	71.7	98	9500	11000	61.5	83.5	82		0.6
NN3012/P5W33-HRB	NN3012K/P5W33-HRB	NN3012K/P4W33-HRB	60	95	26		86.1	72.9	98.8	9000	10000	66.5	88.5	87	1	0.63
NN3013/P5W33-HRB	NN3013K/P5W33-HRB	NN3013K/P4W33-HRB	65	100			91	82.6	112	8500	9500	71.5	93.5	92		0.68
—	NN3014K/P5W33-HRB	NN3014K/P4W33-HRB	70	110		1.1	100	94.7	136	7500	8500	76.5	103.5	101		0.98
NN3015/P5W33-HRB	NN3015K/P5W33-HRB	NN3015K/P4W33-HRB	75	115			105	95.9	142	7000	8000	81.5	108.5	106		1.02
NN3016/P5W33-HRB	NN3016K/P5W33-HRB	NN3016K/P4W33-HRB	80	125			113	120	178	6700	7500	86.5	118.5	114		1.42
NN3017/P5W33-HRB	NN3017K/P5W33-HRB	NN3017K/P4W33-HRB	85	130			118	124	192	6300	7000	91	123.5	119		1.5
NN3018/P5W33-HRB	NN3018K/P5W33-HRB	NN3018K/P4W33-HRB	90	140			127	140	227	6000	6700	98		129		1.94
—	NN3019K/P5W33-HRB	NN3019K/P4W33-HRB	95	145	37	1.5	132	143	237	5600	6300	103	132	134	1.5	2.02
NN3020/P5W33-HRB	NN3020K/P5W33-HRB	NN3020K/P4W33-HRB	100	150			137	153	260	5300	6000	108	142	139		2.12
NN3021/P5W33-HRB	NN3021K/P5W33-HRB	NN3021K/P4W33-HRB	105	160	41		146	190	306	5000	5600	114	151	148		2.66
NN3022/P5W33-HRB	NN3022K/P5W33-HRB	NN3022K/P4W33-HRB	110	170	45		155	221	358	4800	5300	119	161	157		3.38
NN3024/P5W33-HRB	NN3024K/P5W33-HRB	NN3024K/P4W33-HRB	120	180	46	2	165	231	388	4500	5000	129	171	167		3.71
NN3026/P5W33-HRB	NN3026K/P5W33-HRB	NN3026K/P4W33-HRB	130	200	52		182	312	495	4000	4500	139	191	183		5.3
NN3028/P5W33-HRB	NN3028K/P5W33-HRB	NN3028K/P4W33-HRB	140	210	53		192	297	516	3800	4300	149	201	194	2	6.12
—	NN3030K/P5W33-HRB	NN3030K/P4W33-HRB	150	225	56		206	334	579	3600	4000	161	214	208		7.54
—	NN3034K/P5W33-HRB	NN3034K/P4W33-HRB	170	260	67		236	438	785	3000	3400	181	249	238		12.5
—	NN3036K/P5W33-HRB	NN3036K/P4W33-HRB	180	280	74	2.1	255	562	986	2800	3200	191	269	257		16.4
—	NN3038K/P5W33-HRB	NN3038K/P4W33-HRB	190	290	75		265	645	1058	2600	3000	201	279	267		17.8
—	NN3040K/P5W33-HRB	NN3040K/P4W33-HRB	200	310	82		282	672	1177	2400	2800	211	299	285		22.5
—	NN3044K/P5W33-HRB	NN3044K/P4W33-HRB	220	340	90	3	310	809	1440	2200	2600	233	327	313	2.5	29.6
—	NN3048K/P5W33-HRB	NN3048K/P4W33-HRB	240	360	92		330	842	1560	2000	2400	253	347	333		32.7
—	NN3052K/P5W33-HRB	—	260	400	104		364	1020	1910	1900	2200	276	384	367		47.7
—	NN3056K/P5W33-HRB	—	280	420	106	4	384	1060	2290	2220	1800	296		404	3	49.7
—	NN3060K/P5W33-HRB	—	300	460	118		418	1290	2790	1200	1500	316	—	444		76.2
—	NN3064K/P5W33-HRB	—	320	480	121		438	1360	2910	1100	1400	336		464		76.3

1Kg=9.81N



请按图示订货

型号
NN3060K/P5W33-HRB
NN3064K/P5W33-HRB



未税价(元)

● 优惠价
数量 1~9 10~
价格 100% 另行报价



交货期
7



总目录
目录
使用说明
螺钉
螺栓
螺柱
铆接类
组合件
螺母
垫圈
挡圈
树脂类
带挡块
螺钉
柱塞
紧固件
进口专区
紧固件
专用配件
经济型
轴承
标准型
轴承
进口型
轴承
品牌轴承
带座轴承
吊环
索具
电子焊接
工具
手动工具
电动工具
气动工具
储存工具
量具
刀具
技术资料