



代码	类型	材质	表面处理
EUX66	直杆短型	S45C	-
EUX67			无电解镀镍



拆卸用螺孔与紧固螺孔位置重叠



视角标准：第一视角

型号		D	H	P.C.D.	H <sub>1</sub>	H <sub>2</sub>	锁紧螺栓				容许最大扭矩(N·m)	容许轴向负载(KN)	重量(g)						
代码	d						M×L	个数	内六角扳手公称尺寸	紧固扭矩(N·m)									
EUX66 EUX67	20	47	26	34.5	20	18	M6×L18	10	5	12.7	300	29.5	240						
	22			34.5							330		230						
	24	50		37.5							410	33.8	250						
	25			430							240								
	28	55		42.5							24	21	M8×L22	14	6	29.4	530	37.8	290
	30																570		280
	32	60		47.5							24	21	M8×L22	14	6	29.4	730	45.4	340
	35																800		310
	38	65		52.5							24	21	M8×L22	14	6	29.4	1010	52.9	370
	40																1060		350
	42	75		60							24	21	M8×L22	12	6	29.4	1560	74.1	600
	45																1670		570
	48	80		65							24	21	M8×L22	12	6	29.4	1780	74.1	630
	50																1860		610
	55	85		70							24	21	M8×L22	14	6	29.4	2530	74.1	660
	60	90		75							24	21	M8×L22	14	6	29.4	2760	91.8	700
65	95	80	24	21	M8×L22	16	6	29.4	2990	91.8	710								



请按图示订货

型号			
代码	d	D	H
EUX66	22	47	26
EUX67	24	50	26

EUX66—d24



未税价(元)

● 优惠价

数量	1~4	5~
价格	100%	另行报价



交货期

5

轴及轮孔部的推荐公差、表面粗糙度

安装面	公差	表面粗糙度
轴外径	h7(g6)	Ra1.6以下
孔轮部内径	H7	Ra3.2以下