


代码	类型		材质	表面处理	焊接方式
ZIP53	裸压着端子	管形接头	紫铜	镀锡	接缝焊银

特点

- 电解铜镀锡，导电性良好；
- 无缝焊接使导体和端子间具有良好的接触性和拉伸强度。



销售方式	每袋数量
袋	见参数表



视角标准：第一视角

代码	型号	规格	适用电线规格		外形尺寸(mm)			包装 (PCS/袋)
			截面面积(mm <sup>2</sup> )	L	D	D <sub>1</sub>	d	
ZIP53	0506	0.5	6	1.3	1.7	1	2000	
	0508	8						
	0510	10						
	0512	12						
	7506	0.75	6	1.5	1.9	1.2		
	7508	8						
	7510	10						
	7512	12						
	1006	1	6	1.7	2.2	1.4	2000	
	1008	8						
	1010	10						
	1012	12						
	1508	1.5	8	2	2.5	1.7		
	1510	10						
	1512	12						
	1518	18						
	2506	2.5	6	2.6	3.3	2.3		
	2508	8						
	2510	10						
	2512	12						
	2518	18						
	4009	4	9	3.2	3.9	2.8	1000	
	4012	12						
	4018	18						
	6010	6	10	3.9	4.7	3.5	500	
	6012	12						
	6018	18						
	1012A	10	12	4.9	5.8	4.5		
	1018	18						
	1612	16	12	6.2	7.2	5.8		
	1618	18						
	1620	20						
	2516	25	16	7.9	9.1	7.5		
2518A	18							
2522	22							
2525	25	25	8.7	10.2	8.3	200		
3516	35	16						
3520	20							
3525	25	25	10.9	12.7	10.3	100		
5018	50	18						
5022	22							
5025	25	25	14.3	15.8	13.5	200		
7022	70	22						
7025	25	25	15.6	17.3	14.8		100	
9525	95	25						



型号		截面面积(mm <sup>2</sup> )
代码	规格	
ZIP53	0506	0.5
	0508	

ZIP53 - 0506

