


代码	类型		材质
ZKW20	高性价比型	D型端子型冷压针	铜合金


关联工具：冷压针压接钳：ZIQ10 (P894)
退针器：ZIQ21-D (P895)



端子类型：M (插针)



端子类型：F (插孔)



视角标准：第一视角

型号		表面材质	适配电线截面积	额定电流	接触电阻	适配插芯
代码	端子类型					DD型超高密度型
ZKW20	M (插针)	G (镀金)	0.37 (0.37mm ²) 0.5 (0.5mm ²) 0.75 (0.75mm ²) 1.0 (1.0mm ²) 1.5 (1.5mm ²) 2.5 (2.5mm ²)	10A	≤3mΩ	ZKW07 (P693)
	F (插孔)					

线规		剥线长度
0.14-0.37mm ²	AWG 26-22	
0.5mm ²	AWG 20	
0.75mm ²	AWG 18	8
1mm ²	AWG 18	
1.5mm ²	AWG 16	
2.5mm ²	AWG 14	6



请按图示订货

型号		表面材质	适配电线截面积
代码	端子类型		
ZKW20	M (插针)	G (镀金)	0.37 (0.37mm ²) 0.5 (0.5mm ²)
	F (插孔)		

ZKW20-M-G-0.37

