代码	类型	材质	硬度	颜色	使用温度范围
NFL51	凝胶胶条	粘弹性人造橡胶	Asker F65	淡黄色	-10~70°C

- ! 涂有氟粉末,以防粘住。
- ! 以卷绕状态交货。
- ! 可用切刀等从正上方切断后使用。







型된	-	
代码	D	L .
	2	
NFL51	5	500 1000 1500
	10	



	型型	3			
,	代码	D			
	QFL5	5	(500)	1000	1500
	NFL51-	– D2 -	- L50	0	







◎ 缓冲带


减震防护类

G3

代码	类型	材质	硬度	颜色
NFL71		乙丙橡胶海绵	Asker C8	黑色
NFL72	缓冲带	硅橡胶海绵	Asker C35	橙色
NFL73	坂/中市	EPDM发泡体	Asker C1以下	黑色
NFL74		氯丁橡胶海绵	Asker C25	無巴

- ! 粘胶耐热温度80℃。
- ① 粘胶层的厚度为0.17~0.20mm。

型号












	ERT
30	1000 1000





代码 NFL71 NFL72 NFL73

_	代码	T	В	
Ł	NFL72	<u>3</u>	15	1000
Į,	NIEL 74	T2 E	110 1	1000

3 5 10



В

10 15 20



○ 胶带

- 4
初免标准: 第一如免
_

型号		D	т.	粘接力	抗拉强度	延伸率	击穿电压
代码	Т	Ь		(N/25mm宽)	(N/25mm宽)	(%)	(KV)
	0.08	13	0.05	6.13	49	200	4.5
NFL91	0.13	25	0.08	9.32	56.4	250	7.5
NFL91	0.18		0.13	10.79	122.6	340	8.2
	0.23	50	0.18	11.52	149.6	360	9



型·	В	
代码	T	B
ØFL93	0	<u>13</u> 25
MFLS	0.13	25
NEL 01_	_ TO O8	B13





