橡胶脚垫


◀ 轴环型/垫圈型

ľ	/ to	类型		材质	į		橡胶硬度	
	代码			橡胶主体	金属零件	面电阻		
ľ	NHY01	/05 导电型	B.由 #1	导电性橡胶	SPCE (镀锌)	小于100ΚΩ	肖氏A65	
	NHY05		守电空					
ľ	NHY11 垫圈型		绝缘型	三元乙丙橡胶	(以(十)	大于1MΩ		


- ① 由于工艺原因,金属零件上可能存在橡胶残留,不影响产品使用。
- ① 由于产品含有老化添加剂,产品表面会持续缓慢析出白色腊质,属于正常现象,不影响产品性能。




轴环型 NHY01




垫圈型 NHY05 NHY11 规格: 10



规格: 15/16/18/20/24/26/30/32



规格: 36



视角标准:第一视角

型号		D	10°	H ₁	D ₁	D ₂	容许负载(N)
代码	规格		OWE	111	Di	D2	台厅贝软(N)
	15	15	9	7	6	3	70
++ ++ ===	20	20	12				160
轴环型 NHY01	30	30	19	10		4	230
MILLOI	32	32	25		14	5	335
	35	35	20	8			420
	10	10	5	3	5	3	100
	15	15	8	4 5	- 6		
	16	16	10				150
	18	18	11	7 5	7		
垫圈型	20	20	12		,	4	200
NHY05 NHY11	24	24	10		9		200
	26	26	15	10	10		300
	30	30	19		14		
	32	32	25	9	14	5	500
	36	36	17		17	6	150









