





代码	材质	表面处理
AOB02	A6063-T6	碱砂氧化
AOB03	A6063-T5	黑色氧化
AOB05		喷砂氧化
AGB06		喷砂电泳

- ④ 提供可选加工服务。
- ⑤ 切断面未进行氧化处理。


AGB06-1525A




AOB05-1530A
AGB06-1530A




AOB03-1530
AOB05-1530
AGB06-1530




AOB02-H1530B




AOB05-1530F



AOB05-1530C



AOB05-1530D



型号	规格	L 最小单位0.5	截面尺寸	每米重量Kg/m (理论值)	截面积 (mm ²)	截面惯性矩		抗弯截面模数	
						I_x	I_y	W_{xmax} (mm ³)	W_{ymax} (mm ³)
AOB02	H1530B	50~6000	15×30	0.70	246.41	0.70×10^4	1.47×10^4	929.87	978.33
AOB03	1530			0.68	241.15	0.69×10^4	1.47×10^4	926.13	976.53
	1530F			0.57	202.59	0.62×10^4	1.43×10^4	827.47	951.07
	1530			0.68	241.15	0.69×10^4	1.47×10^4	926.13	976.53
AOB05	1530C			0.60	213.16	0.62×10^4	1.10×10^4	829.47	733.00
	1530A			0.42	148.95	0.52×10^4	1.18×10^4	689.87	789.13
	1530D		0.68	240.70	0.669×10^4	1.585×10^4	892.26	1056.82	
	1525A		0.33	119.26	0.36×10^4	0.61×10^4	498.75	491.28	
AGB06	1530A		0.42	148.95	0.52×10^4	1.18×10^4	689.87	789.13	
	1530		0.68	241.15	0.69×10^4	1.47×10^4	926.13	976.53	

- ④ 提供来图加工服务。
- ⑤ 通用铝型材使用配件选型表

槽口类型	适用配件
	选用国标30系列型材配件
	选用国标40系列型材配件



请按图示订货

型号		L 最小单位0.5
代码	规格	
AOB05	1530F	50<D00
	1530	
AOB05-1530F-L400		