∢ 条纹把手・塑料

∢ 压入式条纹把手・聚缩醛



	代码	类型	ı	握柄部		螺纹部	
l	1749			材质	颜色	材质	表面处理
l	HAV11		外螺纹型			1215MS	镀锌
l	HAV12	条纹把手	7) 塚纹空	PA6	黑色	SUS304	
l	HAV16	余纹拉士	中間(立田)	PAO	無巴	黄铜	_ ~ ∧
ı	HAV17		内螺纹型			SUS304	




外螺纹型 HAV11 HAV12











○ 外螺纹型


型号 代码	. M	D	L	D ₁	Н	h ₁	参考重量 (kg/pcs)
	<u>4</u> 5	20	10 15 20 10 15 20	12	13.5	5.5	0.01
HAV11	6	25	20 30	15	19.5	10.5	
	8	30	20 30 40	18	21.5		0.020
	10	35	20 30 40	21	28	15	0.020
	5	20	10 15 20	12	13.5	5.5	0.010
HAV12	6	25	10 20 30	15	19.5	10.5	0.010
	8	30	20 30 40	18	28	17	0.020
					*		

🧿 内螺纹型

型号		D	D ₁	н	[®] h	h ₁	参考重量
	M						(kg/pcs)
	(4)	20	12	13.5	₩ 11	5.5	
HAVAG	5		12	10.0		0.0	
HAV16 HAV17	6	25	15	19.5		10.5	0.01
11/5/17	8	30	18	21.5	14	10.5	
	10	35	21	28	16.5	15	

① HAV17无 () 内规格。














☑ 压入式条纹把手

代码 HAV2	类型 1 压入式条纹把手	材质 POM			
	5场售的内六角螺栓,	经压入结合后使用。		◎ 安装范例:	
	武选定螺纹长度。 3工具紧固。				
<u>.</u> ₩207	11. 大苏凹。)T [7] [8] (4))T [7] [8] [4]		
		适用螺栓: M3~M6	适用螺栓: M8		库存
			7/////		
	(mon				
1 4	- } - } - }				
//	In Ind				
	·	<u>h1</u>	h1_	① 压入时,必须垂直插入,	
		H -	- H -	否则可能损坏!	视角标准:第一视角

型号 代码 适用螺栓M		把手颜色	D	D ₁	Н	h ₁	参考破坏扭矩 (N·m)	参考重量 (kg/pcs)	
	3	E(黑色) H(灰色)	9.5	8.3	4.5	0.5	0.5		
	4		13	9.8	5.5	1.5	1.5		
HAV21	5			16	11.5	6.6	2.1	2.7	0.01
	6			19	13	7.5	2	2.8	
	8		26	16	10.2	3	4.5		







● 优惠价							
数量	1~9	10~					
价格	100%	另行报价					

