## 固定型/平底活动型 ▶

\_\_\_\_ 容许载荷120~160kg


## 工业脚轮



	代码		3	支架	轮部						
	I CIHJ	类型	材质	表面处理	刹车类型	北印					
	J-CPF01	固定型	Q235A	镀锌	_	代号 UH	材质 聚氨酯	颜色 黑色	轴承		
l		回定主	2230/1			RC	橡胶	灰色	双轴承		











	C1 A
피마	


型号		轮部	н	_	_	В		C <sub>1</sub>	Œ	d	容许载荷 (kg)	参考重量
代码	D	代号		Г	A	ь	C	C1	8			(kg)
	100	UH	130	29							120	0.85
J-CPF01		BC.	130	34	92	69.5	77.8	71.4	44.5	9	120	0.81
	125	RC	157	32				ムレ	茶		160	0.85

塑料双刹

## ◎ 平底活动型


代码			支架	轮部						
1 (1)=3	类型	材质	表面处理	刹车类型		#6	пÞ	动		
J-CPG01	平底	Q235A	镀锌	_	代号	材质	颜色	轴承		
J-CPG02	活动型	Q235A		塑料双刹	RC	聚氨酯橡胶	<b>黑色</b> 灰色	双轴承		







无刹 J-CPG01















型号														参考重量(kg)												
代码	D	轮部	Н	Н	Н	Н	Н	Н	Н	Н	Н	Н	F	Α	В	С	C <sub>1</sub>	E	E <sub>1</sub>	d	R	容许载荷   (kg)	J-CF	PG01	J-CF	PG02
1 (1)=	D	代号											UH	UH	RC	UH	RC									
无刹	100	UH	120	29			// //	OER.				80	400	0.97	_	1.27										
J-CPG01 塑料双刹	3-CF G0 I	RC	130	34	96	78	80	76.2	60	45	9	00	120		0.85		1.23									
J-CPG02	125	KC.	157	32			410,				97.5	160	_	0.97		1.3										









